

ROUTE MASTER AT

SUV / Light Truck All-Terrain



M+S **40K**
warranty

Standard warranty for P-Metric only.

Route Master AT offers exceptional traction and durability without compromising comfort.

- UTQG : 520/A/B (P-Metric)



P-Metric

INCH	S-CODE	SIZE	L/I & S/S	MEASURING RIM	RIM WIDTH RANGE	MAXIMUM		OVERALL DIAMETER	SECTION WIDTH	TREAD WIDTH	TREAD DEPTH	REVS/ MILE	SIDEWALL TYPE	PRICE	
						AIR (PSI)	LOAD (LBS)								
15	1012060	P235/75R15 XL	108T	6.5	6-8	50	2,183	28.9	9.3	6.9	12.0	718.85	OWL	190.33	
	16	1012061	P235/70R16	104T	7.0	6-8	51	1,984	29.0	9.5	7.2	12.5	716.81	OWL	207.76
		1012062	P245/70R16	106T	7.0	6-8	51	2,094	29.5	9.8	7.3	12.5	703.46	OWL	220.56
		1012063	P255/70R16	109T	7.5	6.5-8.5	51	2,271	30.1	10.7	7.6	12.5	690.60	OWL	231.88
		1012064	P265/70R16	111T	8.0	7-9	51	2,403	30.6	10.7	8.0	12.5	678.20	OWL	241.43
		1012065	P245/75R16	109T	7.0	6.5-8	51	2,271	30.5	9.8	7.3	12.5	680.82	OWL	217.78
		1012066	P265/75R16	114T	7.5	7-9	51	2,601	31.6	10.5	8.0	12.5	656.34	OWL	233.48
17	1012067	P245/65R17	105T	7.0	7-8.5	51	2,039	29.5	9.8	7.6	12.5	703.46	OWL	246.77	
	1012068	P265/65R17	110T	8.0	7.5-9.5	51	2,337	30.6	10.7	8.1	12.5	679.07	SBL	262.23	
	1012069	P245/70R17	108T	7.0	6.5-8	51	2,205	30.6	9.8	7.3	12.5	679.97	OWL	256.64	
	1012070	P255/70R17	110T	7.5	6.5-8.5	51	2,337	31.1	10.2	7.6	12.5	667.95	OWL	264.34	
	1012071	P265/70R17	113T	8.0	7-9	51	2,535	31.6	10.7	8.0	12.5	656.34	OWL	273.10	
18	1012072	P275/65R18	114T	8.0	7.5-9.5	51	2,601	32.1	11.0	8.4	12.5	646.62	SBL	278.56	

OWL : Outline White Letters
SBL : Serrated Black Letters

LT-Metric

INCH	S-CODE	SIZE	PLY RATING	L/I & S/S	MEASURING RIM	RIM WIDTH RANGE	MAXIMUM		OVERALL DIAMETER	SECTION WIDTH	TREAD WIDTH	TREAD DEPTH	REVS/ MILE	SIDEWALL TYPE	PRICE	F.E.T
							AIR (PSI)	LOAD (LBS)								
15	2001796	LT235/75R15	6	104/101R	6.5	6-7	S 50 D 50	1985 1820	28.9	9.3	7.1	16.0	720	OWL	203.02	
	2001809	31X10.50R15	6	109R	8.5	7-9	S 50 D 50	2270 -	30.5	10.5	8.1	16.0	681	OWL	252.80	
16	2001797	LT225/75R16	10	115/112S	6.0	6-7	S 80 D 80	2680 2470	29.3	8.8	6.9	15.5	709	SBL	241.97	
	2001798	LT245/75R16	10	120/116S	7.0	6.5-8	S 80 D 80	3042 2778	30.5	9.8	7.4	16.0	682	SBL	268.76	
	2001799	LT265/75R16	10	123/120R	7.5	7-8	S 80 D 80	3415 3085	31.6	10.5	8.3	16.0	656	SBL	282.29	
	2001800	LT285/75R16	10	126/123R	8.0	7.5-9	S 80 D 80	3750 415	32.8	11.3	8.6	16.0	633	OWL	301.58	2.36
	2001801	LT235/85R16	10	120/116R	6.5	6-7.5	S 80 D 80	3415 3085	31.7	9.3	7.0	16.0	655	SBL	259.63	
17	2001802	LT245/70R17	10	119/116R	7.0	6.5-8	S 80 D 80	3000 2755	30.6	9.8	7.4	16.0	680	SBL	293.41	
	2001803	LT265/70R17	10	121/118S	8.0	7-8.5	S 80 D 80	3195 2910	31.6	10.7	8.1	15.5	656	OWL	306.61	
	2001805	LT245/75R17	10	121/118S	7.0	6.5-7.5	S 80 D 80	3195 2910	31.5	9.8	7.4	15.5	660	OWL	304.24	
	2001806	LT235/80R17	10	120/117R	6.5	6-7.5	S 80 D 80	3085 2835	31.8	9.3	7.1	16.0	653	SBL	295.04	
	2001815	LT285/70R17	10	121/118S	8.5	7.5-9	S 80 D 80	3195 2910	32.8	11.5	8.7	16.0	634	OWL	331.14	
18	2001817	LT275/65R18	10	123/120S	8.0	7.5-9.5	S 80 D 80	3415 3085	32.1	11.0	8.3	16.0	647	SBL	314.71	
	2001818	LT275/70R18	10	125/122S	8.0	7-8.5	S 80 D 80	3640 3305	33.2	11.0	8.3	15.5	626	SBL	317.89	1.32

OWL : Outline White Letters
OBL : Outline Black Letters