

The tire that invented the all-terrain category, setting the standard for on- and off-road performance.

Fast Facts: A bold look that transforms the appearance of any vehicle.
Choice of distinctive raised white letters or black outline sidewall styling.

Maximum all-terrain traction.

ShoulderLock™ technology with 40% wider shoulder grooves increases traction and control in aired-down driving.

Incredible sidewall strength.

Three-ply polyester carcass guards against punctures and bruises under the tread and in the sidewall.

Designed to last.

Improved stress distribution for increased tread life and enhanced resistance to irregular wear.

Features:

- Aggressive, high-void all-terrain tread design with interlocking tread elements, innovative siping and stabilized tread center
- Dual-compound tread
- Three-ply polyester carcass–TriGard[®] construction
- High-strength single strand bead construction
- Two full-width steel belts
- Rim protector

Benefits:

- Excellent traction and handling on- and off-road; improved traction; and decreased stone retention†
- Exceptional bruise resistance under the tread and in the sidewall
- Stiffer tread area for precise steering response and better cornering control; excellent puncture and bruise resistance†
- Helps protect wheel and tire from off-road hazards, especially during aired-down driving
- Long life and increased durability†
- Improved ride and increased bead strength†

† Compared to Radial All-Terrain T/A[®]



Meets the RMA* Severe Snow Traction performance requirements
*Rubber Manufacturers Association

Tire Size	Service Desc.	Sidewall	MSPN	Rim Width Range (in.)	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth (in/32nds)	Rev/Mile at 45 mph	Max Load Single (lbs@psi)	Max Load Dual (lbs@psi)	OE Fitments
LT195/75R14/D	99R	RWL	34557	5.0 - 6.0	7.7 on 5.5	25.5	16.0	815	1710@65		
LT215/75R15/C	100S	RWL	02821	5.5 - 7.0	8.4 on 6.0	27.8	16.0	748	1765@50	1610@50	
LT235/75R15/C	104S	RWL	29274	6.0 - 7.0	9.1 on 6.5	29.0	16.0	717	1985@50	1820@50	
30x9.50R15/C	104S	RWL	16177	6.5 - 8.5	9.4 on 7.5	29.5	16.0	705	1990@50		
31x10.50R15/C	109S	RWL	89796	7.0 - 9.0	10.5 on 8.5	30.7	16.0	677	2250@50		
32x11.50R15/C	113R	RWL	61107	8.0 - 10.0	11.4 on 9.0	31.7	17.0	656	2530@50		
33x10.50R15/C	114R	RWL	63540	7.0 - 9.0	10.6 on 8.5	32.7	16.0	636	2620@50		
33x12.50R15/C	108R	RWL	09681	8.5 - 11.0	12.4 on 10.0	32.7	17.0	636	2225@35		
33x9.50R15/C	113R	RWL	32374	6.5 - 8.5	9.5 on 7.5	32.7	16.0	636	2510@50		
35x12.50R15/C	113R	RWL	49774	8.5 - 11.0	12.7 on 10.0	34.7	17.0	599	2555@35		
LT215/70R16/C	100R	RWL	42014	5.5 - 7.0	8.7 on 6.5	28.0	16.0	743	1765@50		
LT225/70R16/C	102R	RWL	02204	6.0 - 7.0	8.9 on 6.5	28.5	16.0	730	1875@50		
LT225/75R16/E	115S	RWL	10761	6.0 - 7.0	8.8 on 6.0	29.3	16.0	710	2680@80	2470@80	
LT235/70R16/C	104S	RWL	72870	6.0 - 7.5	9.5 on 7.0	29.1	16.0	715	1985@50	1820@50	
LT235/85R16/E	120S	RWL	10416	6.0 - 7.0	9.4 on 6.5	31.7	16.0	656	3042@80	2778@80	
LT245/70R16/D	113S	RWL	03219	6.5 - 7.5	9.8 on 7.0	29.5	16.0	705	2535@65		
LT245/75R16/E	120S	RWL	11379	6.5 - 8.0	9.8 on 7.0	30.5	16.0	682	3042@80	2778@80	
LT255/70R16/D	115S	RWL	78762	6.5 - 8.0	10.2 on 7.5	30.2	16.0	689	2680@65	2470@65	
LT265/70R16/D	117S	RWL	42637	7.0 - 8.5	10.6 on 8.0	30.7	16.0	675	2835@65		
LT265/75R16/E	123Q	BSW	71887*	7.0 - 8.0	10.5 on 7.5	31.8	15.0	654	3415@80	3085@80	
LT265/75R16/E	123S	RWL	20679	7.0 - 8.0	10.5 on 7.5	31.7	16.0	657	3415@80	3085@80	
LT275/70R16/D	119S	RWL	94223	7.0 - 8.5	11.1 on 8.0	31.2	16.0	667	3000@65		
LT285/75R16/D	122R	RWL	77118	7.5 - 9.0	11.4 on 8.0	32.8	17.0	634	3305@65		
LT285/75R16/E	126Q	BSW	87606*	7.5 - 9.0	11.3 on 8.0	33.0	15.0	630	3750@80	3415@80	
LT295/75R16/D	123R	RWL	92042	7.5 - 9.5	11.5 on 8.0	33.2	17.0	626	3415@65		
LT305/70R16/E	124R	RWL	33393	8.0 - 9.5	12.2 on 9.0	33.0	16.0	630	3525@65		
LT315/75R16/D	121Q	RWL	03643	8.0 - 10.0	12.2 on 8.5	34.6	17.0	601	3195@50		
33x12.50R16.5/D	118R	RWL	30537	8.25 - 10.5	12.4 on 9.75	32.6	17.0	638	2910@50		
35x12.50R16.5/D	123R	RWL	56149	8.25 - 10.5	12.6 on 9.75	34.6	17.0	601	3415@50		
LT225/70R17/D	110S	RWL	08725	6.0 - 7.5	9.0 on 6.5	29.6	16.0	703	2335@65		
LT235/80R17/E	120R	RWL	27039*	6.0 - 7.5	9.3 on 6.5	31.8	16.0	654	3085@80	2835@80	
LT245/70R17/E	119R	RWL	34162*	6.5 - 8.0	9.8 on 7.0	30.6	16.0	681	3000@80	2755@80	
LT245/75R17/E	121R	RWL	10209	6.5 - 7.5	9.8 on 7.0	31.6	16.0	658	3195@80	2910@80	
LT265/65R17/E	120S	RWL	01616	7.5 - 9.5	10.7 on 8.0	30.7	15.0	678	3085@80		
LT265/70R17/C	112R	RWL	12665	7.0 - 8.5	10.7 on 8.0	31.8	16.0	654	2470@50		
LT265/70R17/E	121R	RWL	55086	7.0 - 8.5	10.7 on 8.0	31.8	16.0	654	3195@80	2910@80	
LT275/65R17/E	121S	RWL	26795	7.5 - 9.5	11.0 on 8.0	31.2	15.0	667	3195@80		
LT275/70R17/E	121R	RWL	02458*	7.0 - 8.5	11.0 on 8.0	32.2	16.0	646	3195@80		
LT285/70R17/E	121Q	RWL	25105	7.5 - 9.0	11.5 on 8.5	32.8	16.0	635	3195@80		
LT285/70R17/D	121R	BSW	37130*	7.5 - 9.0	11.0 on 8.0	32.7	16.0	636	3195@65		DC
LT305/65R17/E	121R	RWL	00875	8.5 - 11.0	12.2 on 9.0	32.7	16.0	636	3195@65	2910@65	
LT315/70R17/D	121R	BSW	54142*	8.5 - 10.0	12.0 on 8.5	34.5	17.0	601	3195@50		GM
LT315/70R17/D	121S	BSW	37164*	8.5 - 10.0	11.8 on 8.5	34.5	17.0	606	3195@50		F
37x12.50R17/D	124R	RWL	12411	8.5 - 11.0	12.8 on 10.0	36.3	17.0	574	3525@50		
LT265/65R18/E	122R	RWL	02625	7.5 - 9.5	10.7 on 8.0	31.7	16.0	656	3305@80		
LT275/65R18/E	123R	RWL	02818*	7.5 - 9.0	11.0 on 8.0	32.1	16.0	648	3415@80		
LT275/70R18/E	125R	RWL	15465*	7.0 - 8.5	11.0 on 8.0	33.2	16.0	627	3640@80	3305@80	
LT285/65R18/E	125R	RWL	67553	8.0 - 10.0	11.5 on 8.5	32.7	16.0	636	3640@80		
LT305/65R18/E	124R	RWL	35237	8.5 - 11.0	12.2 on 9.0	33.7	16.0	617	3525@65		

All-Terrain T/A[®] KO cont.

Tire Size	Service Desc.	Sidewall	MSPN	Rim Width Range (in.)	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth (in/212185)	Rev/Mile at 45 mph	Max Load Single (lbs@psi)	Max Load Dual (lbs@psi)	O.E. Fitments
LT325/65R18/E	127R	RWL	05968	9.0 - 12.0	13.0 on 9.5	34.6	16.0	601	3860@65		
37x12.50R18/D	123R	RWL	39925	8.5 - 11.0	12.5 on 10.0	36.6	17.0	568	3415@50		
LT275/65R20/E	126S	RWL	11420*	7.5 - 9.5	11.0 on 8.0	34.1	16.0	610	3750@80		
LT285/55R20/D	117T	RWL	30710	8.0 - 10.0	11.7 on 9.0	32.5	15.0	640	2835@65		
LT285/65R20/E	127S	RWL	33774	8.0 - 10.0	11.5 on 8.5	34.7	15.0	599	3860@80		
LT305/55R20/E	121S	RWL	30836	8.5 - 11.0	12.4 on 9.5	33.4	15.0	623	3195@65	2910@65	
LT325/60R20/E	126R	RWL	38941	9.0 - 12.0	13.0 on 9.5	35.4	15.0	588	3750@65		
37x12.50R20/D	120S	RWL	74497	8.5 - 11.0	12.5 on 10.0	36.6	15.0	568	3085@50		
LT325/50R22/E	122S	BSW	35959	9.0 - 12.0	13.2 on 10.0	35.0	15.0	594	3305@65		
LT325/60R22/D	123S	BSW	25271	9.0 - 12.0	13.0 on 9.5	37.5	15.0	555	3415@50		

Original Equipment Key: DC=Daimler-Chrysler, GM=General Motors, F = Ford

*Size does not meet the RMA requirements for severe snow conditions.

1. The sizes shown are average design values for tires measured on specified measuring rim widths. Some tires may vary from this value by +/-3% of the section height (affecting overall diameter), and +/-4% of the section width.
2. Section width varies approximately 0.2" (5mm) for every 0.5" change in rim width.

WARNING: Serious or fatal injury may result from tire failure due to underinflation or overloading. To ensure correct air pressure and vehicle load, refer to vehicle owner's manual or tire information placard on the vehicle. Serious injury or death may result from explosion of tire/rim assembly due to improper mounting. Only tire professionals should mount tires and they should never inflate beyond 40 psi to seat the beads. Before mixing types of tires in any configuration on any vehicle, be sure to check the vehicle owner's manual for its recommendations.



Meets the RMA* Severe Snow Traction performance requirements
*Rubber Manufacturers Association

DANGER: Never mount a 16" diameter tire on a 16.5" rim.
DANGER: Never mount a 17" diameter tire on a 17.5" rim.

Inflation pressure increase must not exceed the maximum pressure branded on the tire sidewall. When a customer requests a replacement tire with a lower speed rating than the original equipment tire, you must clearly communicate to him or her that the handling of the vehicle may be different, and that its maximum speed capability is limited to that of the lowest speed rated tire on the vehicle. Exceeding the lawful speed limit is neither recommended nor endorsed.

For high-speed driving, additional inflation pressure and possibly reduced tire loading and/or upsizing is required. In the absence of specific recommendations by the vehicle manufacturer, use the following guidelines based on those in the European Tyre and Rim Technical Organization Standards Manual.

For speeds over 100 mph (160 km/h), load and inflation must be adjusted according to the table below.

Q-Speed Rated Sizes:
Maximum Speed (mph) 100
Inflation Increase (psi) 0.0
Load Capacity (% of max.) 100

R-Speed Rated Sizes:
Maximum Speed (mph) 100 106
Inflation Increase (psi) 0.0 1.0
Load Capacity (% of max.) 100 00

S-Speed Rated Sizes:
Maximum Speed (mph) 100 106 112
Inflation Increase (psi) 0.0 1.0 2.0
Load Capacity (% of max.) 100 100 100

T-Speed Rated Sizes:
Maximum Speed (mph) 100 106 112 118
Inflation Increase (psi) 0.0 1.0 2.0 3.0
Load Capacity (% of max.) 100 100 100 100

