

BFGoodrich® All-Terrain T/A® KO2

Our toughest all-terrain tire. Ever.



- **20% Tougher Sidewalls¹**
Featuring race-proven CoreGard™ Technology to take on the toughest road hazards with confidence.
- **Lasts 2X longer on Gravel^{2,3}**
To extend your adventure.
- **10% Better Traction in Mud; 19% Improved Traction in Snow^{4,5}**
Exceeds RMA (Rubber Manufacturers Association) Severe Snow Traction performance requirements, to confidently get you where you want to go.

¹ Improvement depends on the size of tire purchased. 20% improvement based on internal sidewall splitting test results derived from a simulated sidewall aggression testing machine (patent pending US20120245859A1) vs. BFGoodrich® All-Terrain T/A® KO tire in size LT265/70R17. Actual on-road results may vary.

² Based on commissioned third-party gravel endurance tests vs. BFGoodrich® All-Terrain T/A® KO tire in size LT265/70R17.

³ Based on internal wear tests vs. BFGoodrich® All-Terrain T/A® KO tire in size LT265/70R17.

⁴ Based on internal subjective mud traction tests vs. BFGoodrich® All-Terrain T/A® KO tire in size LT265/70R17.

⁵ Based on commissioned third-party snow traction tests vs. BFGoodrich® All-Terrain T/A® KO tire in size LT265/70R17 using the ASTM F1805 test.

Features and Benefits of All-Terrain T/A® KO2 Tires:

- **Tougher sidewall rubber** Split- and bruise-resistant sidewall rubber is derived from BFGoodrich's race-proven Baja T/A® KR2 tire.
- **Thicker, extended shoulder rubber** Increased rubber thickness extending down the sidewall protects more of the critical sidewall failure zone.
- **Advanced deflection design** Computer-predicted object path design deflects protruding objects from snagging and splitting the sidewall.
- **Advanced footprint** Advanced shape more evenly distributes stress for longer, more uniform wear.
- **Side biter lugs** Protruding sidewall rubber blocks provide increased mud, snow and rock traction, especially in aired-down driving situations.
- **Mud-buster bars** Raised bars in the shoulder tread area help release compacted mud for enhanced traction in muddy and soft soil conditions.



ALL-SEASON TIRE



WINTER TIRE



Meets the Rubber Manufacturers Association (RMA) Severe Snow Traction performance requirements.

2X the treadlife on gravel^{2,3}

10% better traction in mud,
19% improved traction in snow^{4,5}

20% tougher sidewalls¹



Popular Replacement Market Fitments:

Ford® F-Series • Jeep® Wrangler • Ford® Expedition • Toyota® Tundra



| Tire Size | Service Desc. | Sidewall | MSPN | Rim Width Range (inches) | Section Width on Measuring Rim Width (inches) | Overall Diameter (inches) | Tread Depth (in/32nds) | Rev/Mile @ 45 mph | Max. Load Single (lbs@psi) | Max. Load Dual (lbs@psi) |
|---------------|---------------|----------|-------|--------------------------|-----------------------------------------------|---------------------------|------------------------|-------------------|----------------------------|--------------------------|
| 30x9.50R15/C | 104S | OORWL | 64055 | 6.5 – 8.5 | 9.5 on 7.5 | 29.5 | 15.0 | 705 | 1990@50 | |
| 31x10.50R15/C | 109S | ORWL | 69948 | 7.0 – 9.0 | 10.6 on 8.5 | 30.5 | 15.0 | 682 | 2270@50 | |
| 32x11.50R15/C | 113R | ORWL | 13079 | 8.0 – 10.0 | 11.4 on 9.0 | 31.5 | 15.0 | 659 | 2535@50 | |
| 33x10.50R15/C | 114R | ORWL | 38370 | 7.0 – 9.0 | 10.6 on 8.5 | 32.5 | 15.0 | 640 | 2600@50 | |
| 33x12.50R15/C | 108R | ORWL | 37881 | 8.5 – 11.0 | 12.5 on 10.0 | 32.5 | 15.0 | 640 | 2205@35 | |
| 34x10.50R17/D | 120R | ORWL | 91644 | 7.0 – 9.0 | 10.6 on 8.5 | 33.5 | 15.0 | 621 | 3085@65 | |
| 34x12.50R18/E | 121R | BSW | 36312 | 8.5 – 11.0 | 12.5 on 10.0 | 33.5 | 15.0 | 621 | 3195@65 | |
| 35x12.50R15/C | 113Q | ORWL | 33572 | 8.5 – 11.0 | 12.5 on 10.0 | 34.5 | 15.0 | 602 | 2535@35 | |
| 35x12.50R17/E | 121R | ORWL | 50022 | 8.5 – 11.0 | 12.5 on 10.0 | 34.5 | 15.0 | 602 | 3195@65 | |
| 35x12.50R18/E | 123R | ORWL | 13389 | 8.5 – 11.0 | 12.5 on 10.0 | 34.5 | 15.0 | 602 | 3415@65 | |
| 37x12.50R17/D | 124R | ORWL | 12987 | 8.5 – 11.0 | 12.5 on 10.0 | 36.5 | 15.0 | 569 | 3525@50 | |
| LT215/65R16/D | 103/100S | BSW | 93878 | 6.0 – 7.5 | 8.7 on 6.5 | 27.0 | 13.0 | 770 | 1930@65 | 1765@65 |
| LT215/70R16/C | 100/97R | ORWL | 37301 | 5.5 – 7.0 | 8.7 on 6.5 | 27.9 | 15.0 | 746 | 1765@50 | 1610@50 |
| LT215/75R15/C | 100/97R | BSW | 30584 | 5.5 – 7.0 | 8.5 on 6.0 | 27.7 | 15.0 | 751 | 1765@50 | 1610@50 |
| LT225/65R17/D | 107/103S | BSW | 95341 | 6.0 – 8.0 | 9.0 on 6.5 | 28.5 | 13.0 | 730 | 2150@65 | 1930@65 |
| LT225/70R16/C | 102/99R | ORWL | 07551 | 6.0 – 7.0 | 9.0 on 6.5 | 28.4 | 15.0 | 732 | 1875@50 | 1710@50 |
| LT225/75R16/E | 115/112S | ORWL | 10598 | 6.0 – 7.0 | 8.8 on 6.0 | 29.3 | 15.0 | 710 | 2680@80 | 2470@80 |
| LT235/70R16/C | 104/101S | ORWL | 33403 | 6.0 – 7.5 | 9.5 on 7.0 | 29.0 | 15.0 | 718 | 1985@50 | 1820@50 |
| LT235/75R15/C | 104/101S | ORWL | 11341 | 6.0 – 7.0 | 9.3 on 6.5 | 28.9 | 15.0 | 721 | 1985@50 | 1820@50 |
| LT235/80R17/E | 120/117S | BSW | 10158 | 6.0 – 7.5 | 9.3 on 6.5 | 31.8 | 15.0 | 654 | 3085@80 | 2835@80 |
| LT235/85R16/E | 120/116S | ORWL | 75445 | 6.0 – 7.5 | 9.3 on 6.5 | 31.7 | 15.0 | 656 | 3042@80 | 2778@80 |
| LT245/65R17/D | 111/108S | ORWL | 52433 | 7.0 – 8.0 | 9.8 on 7.0 | 29.5 | 13.0 | 704 | 2405@65 | 2205@65 |
| LT245/70R16/D | 113/110S | ORWL | 28855 | 6.5 – 7.0 | 9.8 on 7.0 | 29.5 | 15.0 | 704 | 2535@65 | 2335@65 |
| LT245/70R17/E | 119/116S | ORWL | 09666 | 6.5 – 8.0 | 9.8 on 7.0 | 30.6 | 15.0 | 681 | 3000@80 | 2755@80 |
| LT245/75R16/E | 120/116S | ORWL | 15477 | 6.5 – 8.0 | 9.8 on 7.0 | 30.5 | 15.0 | 683 | 3042@80 | 2778@80 |
| LT245/75R17/E | 121/118S | ORWL | 26470 | 6.5 – 7.5 | 9.8 on 7.0 | 31.5 | 15.0 | 660 | 3195@80 | 2910@80 |
| LT255/55R18/D | 109/105R | BSW | 75389 | 7.0 – 9.0 | 10.4 on 8.0 | 29.0 | 13.0 | 717 | 2270@65 | 2040@65 |
| LT255/70R16/E | 120/117S | ORWL | 65289 | 6.5 – 8.0 | 10.2 on 7.5 | 30.1 | 15.0 | 691 | 3085@80 | 2835@80 |
| LT255/70R17/E | 121/118S | BSW | 37495 | 6.5 – 9.8 | 10.2 on 7.5 | 31.1 | 15.0 | 669 | 3195@80 | 2910@80 |
| LT255/70R18/D | 117/114S | BSW | 03020 | 6.5 – 8.5 | 10.2 on 7.5 | 32.1 | 15.0 | 648 | 2835@65 | 2600@65 |
| LT265/60R18/E | 119/116S | BSW | 63681 | 7.5 – 9.5 | 10.7 on 8.0 | 30.5 | 15.0 | 682 | 3000@80 | 2755@80 |
| LT265/65R17/E | 120/117S | ORWL | 16681 | 7.5 – 9.5 | 10.7 on 8.0 | 30.6 | 15.0 | 681 | 3085@80 | 2835@80 |
| LT265/65R18/D | 117/114R | ORWL | 14500 | 7.5 – 9.5 | 10.7 on 8.0 | 31.5 | 15.0 | 659 | 2835@65 | 2600@65 |
| LT265/65R18/E | 122/119R | ORWL | 05260 | 7.5 – 9.5 | 10.7 on 8.0 | 31.5 | 15.0 | 659 | 3305@80 | 3000@80 |
| LT265/70R16/E | 121/118S | ORWL | 62023 | 7.0 – 8.5 | 10.7 on 8.0 | 30.6 | 15.0 | 679 | 3195@80 | 2910@80 |
| LT265/70R17/C | 112/109S | ORWL | 66255 | 7.0 – 8.5 | 10.7 on 8.0 | 31.7 | 15.0 | 657 | 2470@50 | 2270@50 |
| LT265/70R17/E | 121/118S | ORWL | 76397 | 7.0 – 8.5 | 10.7 on 8.0 | 31.7 | 15.0 | 657 | 3195@80 | 2910@80 |
| LT265/70R18/E | 124/121R | ORWL | 40855 | 7.0 – 9.0 | 10.7 on 8.0 | 32.6 | 15.0 | 637 | 3525@80 | 3195@80 |
| LT265/75R16/D | 119/116R | ORWL | 33951 | 7.0 – 8.0 | 10.5 on 7.5 | 31.7 | 15.0 | 657 | 3000@65 | 2755@65 |
| LT265/75R16/E | 123/120R | ORWL | 67179 | 7.0 – 8.0 | 10.5 on 7.5 | 31.7 | 15.0 | 657 | 3415@80 | 3085@80 |
| LT275/55R20/D | 115/112S | BSW | 12579 | 7.5 – 9.5 | 11.2 on 8.5 | 31.9 | 15.0 | 652 | 2680@65 | 2470@65 |
| LT275/60R20/D | 119/116S | BSW | 64811 | 7.5 – 9.5 | 11.0 on 8.0 | 33.0 | 15.0 | 630 | 3000@65 | 2755@65 |
| LT275/65R17/E | 121/118S | ORWL | 42347 | 7.5 – 9.5 | 11.0 on 8.0 | 31.1 | 15.0 | 669 | 3195@80 | 2910@80 |
| LT275/65R18/E | 123/120R | ORWL | 36457 | 7.5 – 9.0 | 11.0 on 8.0 | 32.1 | 15.0 | 648 | 3415@80 | 3085@80 |
| LT275/65R20/E | 126/123S | BSW | 17764 | 7.5 – 9.5 | 11.0 on 8.0 | 34.1 | 15.0 | 610 | 3750@80 | 3415@80 |
| LT275/70R16/D | 119/116S | ORWL | 97884 | 7.0 – 8.5 | 11.0 on 8.0 | 31.2 | 15.0 | 667 | 3000@65 | 2755@65 |
| LT275/70R17/E | 121/118R | ORWL | 76597 | 7.0 – 8.5 | 11.0 on 8.0 | 32.2 | 15.0 | 646 | 3195@80 | 2910@80 |
| LT275/70R18/E | 125/122R | ORWL | 80867 | 7.0 – 8.5 | 11.0 on 8.0 | 33.2 | 15.0 | 627 | 3640@80 | 3305@80 |
| LT285/55R20/D | 117/111T | BSW | 03638 | 8.0 – 10.0 | 11.7 on 9.0 | 32.3 | 15.0 | 643 | 2835@65 | 2600@65 |
| LT285/60R18/D | 118/115S | ORWL | 99506 | 8.0 – 10.0 | 11.5 on 8.5 | 31.5 | 15.0 | 661 | 2910@65 | 2680@65 |
| LT285/65R18/E | 125/122R | ORWL | 93857 | 8.0 – 10.0 | 11.5 on 8.5 | 32.6 | 15.0 | 639 | 3640@80 | 3305@80 |
| LT285/65R20/E | 127/124S | BSW | 88423 | 8.0 – 10.0 | 11.5 on 8.5 | 34.6 | 15.0 | 602 | 3860@80 | 3525@80 |
| LT285/70R17/E | 121/118R | ORWL | 99728 | 7.5 – 9.0 | 11.5 on 8.5 | 32.8 | 15.0 | 635 | 3195@80 | 2910@80 |
| LT285/75R16/C | 116/113R | ORWL | 68012 | 7.5 – 9.0 | 11.3 on 8.0 | 32.8 | 15.0 | 634 | 2755@50 | 2535@50 |
| LT285/75R16/E | 126/123R | ORWL | 05855 | 7.5 – 9.0 | 11.3 on 8.0 | 32.8 | 15.0 | 634 | 3750@80 | 3415@80 |
| LT295/75R16/E | 128/125R | ORWL | 99926 | 7.5 – 9.5 | 11.6 on 8.0 | 33.4 | 15.0 | 623 | 3970@80 | 3640@80 |
| LT305/55R20/E | 121/118S | BSW | 64746 | 8.5 – 11.0 | 12.4 on 9.5 | 33.2 | 15.0 | 626 | 3195@65 | 2910@65 |
| LT305/65R17/E | 121/118R | ORWL | 48785 | 8.5 – 11.0 | 12.2 on 9.0 | 32.6 | 15.0 | 638 | 3195@65 | 2910@65 |
| LT305/65R18/E | 124/121R | BSW | 08017 | 8.5 – 11.0 | 12.2 on 9.0 | 33.6 | 15.0 | 619 | 3525@65 | 3195@65 |
| LT305/70R16/E | 124/121R | ORWL | 34102 | 8.0 – 9.5 | 12.2 on 9.0 | 32.8 | 15.0 | 634 | 3525@65 | 3195@65 |
| LT315/70R17/E | 121/118S | BSW | 08806 | 8.0 – 11.0 | 12.7 on 9.5 | 34.4 | 15.0 | 604 | 3195@65 | 2910@65 |
| LT315/75R16/E | 127/124R | ORWL | 50203 | 8.0 – 11.0 | 12.3 on 8.5 | 34.6 | 15.0 | 602 | 3860@65 | 3525@65 |
| LT325/60R20/E | 126/123S | BSW | 70069 | 9.0 – 12.0 | 13.0 on 9.5 | 35.4 | 15.0 | 588 | 3750@65 | 3415@65 |
| LT325/65R18/E | 127/124R | ORWL | 01547 | 9.0 – 12.0 | 13.0 on 9.5 | 34.6 | 15.0 | 601 | 3860@65 | 3525@65 |