



DUELER™ A/T REVO WITH UNI-T AQ II™

With its powerful grip and smooth ride, the Dueler A/T REVO is the light truck and SUV tire that's equipped for the best and worst of driving conditions. Thanks to the advanced technology, it lets you handle the wet, the dry, even the snow, as the tire wears. With its aggressive tread and sidewall design, even the look of the Dueler A/T REVO grabs attention wherever you go.

WARRANTY SUMMARY

50,000 MILE LIMITED TREADWEAR WARRANTY†

PLATINUM PACT LIMITED WARRANTY††

BUY & TRY 30 DAY GUARANTEE‡



†Prorated replacement if warranted mileage not attained; actual tread life may vary. Certain restrictions and limitations may apply. Ask your retailer for details.

††Replacement at no charge (excluding taxes and disposal fees) if your Bridgestone tire becomes unusable for any reason within the manufacturer's control for up to 3 years from date of purchase or 4 years from date of manufacture, whichever is to the owner's advantage. Certain restrictions and limitations may apply.

‡Original proof of purchase required to take advantage of the 30 Day Test Drive. Tires must be returned within 30 days of purchase. Does not apply to tires supplied as original equipment on new vehicles.





Super EPO

Super EPO goes beyond EPO in providing wet handling as the tire wears. The interactive elements are Super EPC and an enhanced version of Dual Layer Tread.

O-BEAD

Improves uniformity and ride comfort through use of a single continuous strand of cable in the bead construction

HES (Hydro Evacuation Surface)

Improves wet traction by reducing flow resistance of water along groove walls

CSC (Consistent Surface Contact)

Improves dry and wet handling, reduces irregular wear, resulting in better ride comfort through tread block design

Spiral Wrap

Provides a higher level of uniformity and high speed capability through use of a continuous nylon wrap

Super EPC

Super EPC consists of advanced technologies, an Anti-Hardening Resin and Link Stabilizing Agent, to help counteract the effects of heat so tires have the flexibility needed for wet performance as they wear.

LL CARBON (LONG LINK)

Helps improve tread wear and resist cracking, chipping and tearing through the use of a special long length carbon structure

Dual Layer Tread

Minimizes the effect of wear on wet tire performance by exposing high grip rubber as the tire wears.

CO-CS (Computer Optimized Component System)

Maximizes tire performance by optimizing the appropriate combination of tread design, casing shape, materials, and construction.

Dueler A/T REVO with UNI-T TIRE SPECIFICATIONS

Size	Service Description	Load Range	Speed Rating	Sidewall Styling	Article Number	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Tread Width	Static Load Radius	Tread Depth (32")	RPM	Tire Weight	UTQG	Limited Mileage Warranty+
P235/65R17	103T		T	OWL	098201	6.5-8.5	7.0	28.5	9.0	7.1	13.0	11.0	731	32	500 A B	50,000
P245/65R17	105T		T	OWL	098218	7.0-8.5	7.0	29.5	9.8	7.4	13.4	12.0	706	37	500 A B	50,000
P275/60R20	114T		T	OWL	098235	7.5-9.5	8.0	33.0	11.0	9.1	15.0	11.0	631		500 A B	50,000
P275/55R20	111T		T	OWL	098252	7.5-9.5	8.5	31.9	11.2	9.2	14.6	11.0	653		500 A B	50,000
LT285/70R17	121/118R	D	R	OWL	211801	7.5-9.0	8.5	32.8	11.5	8.8	15.2	17.0	635	55		
LT245/70R17	119/116R	E	R	OWL	211818	6.5-8.0	7.0	30.6	9.8	7.5	14.3	15.0	681	49		
LT245/75R17	121/118S	E	S	OWL	211835	6.5-7.5	7.0	31.5	9.8	7.4	14.7	17.0	661	49		
P225/75R15	102S		S	OWL	110043	6.0-7.5	6.0	28.3	8.9	6.7	12.6	13.0	736	31	500 A B	50,000
P235/75R15	105S		S	OWL	110051	6.0-8.0	6.5	28.9	9.4	6.8	12.8	13.0	721	34	500 A B	50,000
P235/70R15	102S		S	OWL	110094	6.0-8.0	7.0	28.0	9.5	6.9	12.5	13.0	744	32	500 A B	50,000
P265/70R15	111S		S	OWL	110108	7.0-9.0	8.0	29.6	10.6	7.8	13.1	13.0	704	39	500 A B	50,000
P245/75R16	109S		S	OWL	110116	6.5-8.0	7.0	30.5	9.8	7.2	13.6	13.0	683	39	500 A B	50,000
P265/75R16	114S		S	OWL	110159	7.0-9.0	7.5	31.9	10.6	7.8	14.1	13.0	653	45	500 A B	50,000
P235/70R16	104S		S	OWL	110183	6.0-8.0	7.0	29.0	9.5	6.9	13.0	13.0	718	34	500 A B	50,000
P245/70R16	106S		S	OWL	110191	6.5-8.0	7.0	29.6	9.8	7.2	13.2	13.0	704	36	500 A B	50,000
P255/70R16	109S		S	OWL	110205	6.5-8.5	7.5	30.1	10.3	7.5	13.4	13.0	694	38	500 A B	50,000
P265/70R16	111S		S	OWL	110213	7.0-9.0	8.0	30.7	10.6	7.8	13.6	13.0	679	41	500 A B	50,000
P235/75R17	108S		S	OWL	044447	6.0-8.0	6.5	30.9	9.2	7.0	13.5	13.0	672	36	500 A B	50,000
P275/70R16	114S		S	OWL	110256	7.0-9.0	8.0	31.2	10.8	8.1	13.8	13.0	668	43	500 A B	50,000
P245/70R17	108S		S	OWL	044430	6.5-8.0	7.0	30.6	9.6	7.3	13.3	13.0	679	36	500 A B	50,000
P255/70R17	110S		S	OWL	044498	6.5-8.5	7.5	31.1	10.1	7.6	13.5	13.0	667	38	500 A B	50,000
P265/70R17	113S		S	OWL	110264	7.0-9.0	8.0	31.7	10.6	7.8	14.1	13.0	657	43	500 A B	50,000
P285/70R17	117T		T	OWL	054188	7.5-9.5	8.5	32.8	11.5	8.4	14.6	11.0	635	43	500 A B	50,000
P255/65R17	108S		S	OWL	044481	7.0-9.0	7.5	30.0	10.5	7.8	13.2	13.0	691	37	500 A B	50,000
P265/65R17	110S		S	OWL	024829	7.5-9.5	8.0	30.5	10.5	8.0	13.7	13.0	683	40	500 A B	50,000
P265/70R18	114T		T	OWL	054205	7.0-9.0	8.0	32.6	10.7	7.8	14.6	11.0	639	41	500 A B	50,000
P275/65R18	114T		T	OWL	068485	7.5-9.5	8.0	32.1	11.0	8.3	14.5	11.0	649	40	500 A B	50,000
30X9.50R15 LT	104S	C	S	OWL	156353	6.5-8.5	7.5	29.6	9.9	7.3	13.7	16.0	704	39		
31X10.50R15 LT	109S	C	S	OWL	156345	7.0-9.0	8.5	30.5	10.9	8.1	14.1	16.0	683	43		
LT235/75R15	104/101S	C	S	OWL	156167	6.0-7.0	6.5	29.0	9.3	7.2	13.5	15.0	718	37		
LT215/85R16	115/112R	E	R	OWL	156183	5.5-7.0	6.0	30.6	8.6	6.3	14.2	16.0	681	44		
LT235/85R16	120/116R	E	R	OWL	156191	6.0-7.0	6.5	32.1	9.3	6.9	14.8	16.0	649	52		
LT225/75R16	115/112R	E	R	OWL	156213	6.0-7.0	6.0	29.5	8.8	6.9	13.7	15.0	706	42		
LT245/75R16	108/104S	C	S	OWL	156221	6.5-7.5	7.0	30.7	9.8	7.5	14.2	15.0	679	41		
LT245/75R16	120/116R	E	R	OWL	156248	6.5-7.5	7.0	30.7	9.8	7.5	14.2	15.0	679	48		
LT265/75R16	112/109S	C	S	OWL	156256	7.0-8.0	7.5	31.8	10.6	8.1	14.7	16.0	655	48		
LT265/75R16	123/120R	E	R	OWL	156302	7.0-8.0	7.5	31.8	10.6	8.1	14.7	16.0	655	54		
LT285/75R16	122/119R	D	R	OWL	156337	7.5-9.0	8.0	33.0	11.5	8.7	15.2	17.0	631	54		
LT265/70R17	121/118R	E	R	OWL	191180	7.0-8.5	8.0	31.6	10.5	8.2	13.7	16.0	656	46		
LT275/65R18	123/120S	E	S	OWL	211767	7.5-9.0	8.0	32.1	11.0	8.0	15.0	16.0	649	52		

†Prorated replacement if warranted mileage not attained; actual tread life may vary. Certain restrictions and limitations may apply. Ask your retailer for details.

