

## BRIDGESTONE

Your Journey, Our Passion

- Aggressive pattern improves traction in all weather conditions.
- Casing construction and cap/base compounding improve durability and retreadability.

M729F

Drive Radial

• Sidewall protector ribs resist cuts and abrasions from curbing and impacts.

Recommended Application

A drive tire recommended for high traction and high scrub applications in: Long Haul Service / Regional Haul Service Pickup & Delivery Service

*Replaces:* Goodyear: G622 Michelin: XDE2+, XDS2

TECHNICAL DATA															
	Load	Material	Weight	Meas.	Overall	Overall	Static Loaded	Overall Width	Revs Per	Tread Depth	Max. Tire Load (Single)		Max. Tire Load (Dual)		Max. Speed
Tire Size	Range	Number	(lbs.)	Rim	Diam.	Width	Radius	(Loaded)	Mile	(32″)	Kg/kPa	Lbs/PSI	Kg/kPa	Lbs/PSI	(MPH)
M729F															
215/75R17.5	F	160-427	60	6.00	30.7	8.5	14.4	9.3	668	22	1700@690	3750@100	1600@690	3525@100	75
225/70R19.5	F	299-839	67	6.00	32.5	8.5	15.3	9.4	639	19	1650@660	3640@95	1550@660	3415@95	75
225/70R19.5	G	227-023	67	6.00	32.5	8.5	15.1	9.4	639	19	1800@760	3970@110	1700@760	3750@110	75
245/70R19.5	Н	227-040	75	7.50	33.4	9.5	15.5	10.5	622	19	2240@830	4940@120	2120@830	4675@120	75
265/70R19.5	G	152-498	88	7.50	34.4	9.9	15.9	10.8	604	19	2500@760	5510@110	2360@760	5205@110	75
285/70R19.5	Н	158-914	98	8.25	35.4	10.6	16.3	11.6	587	20	2900@860	6395@125	2725@860	6005@125	75

• All dimensions taken with tire on measuring rim.

- Loaded dimensions and RPM measured at maximum dual load.
- For load and inflation tables see pages 91 through 96.
- For minimum dual spacing and approved rim widths see page 74.
- For ply ratings see table on page 72.

Bridgestone tires and tubes are subject to an ongoing development program. Bridgestone Americas Tire Operations, LLC retains the right to amend specifications at any time without notice or obligations. Please refer to rim manufacturer's load and inflation limits. Never exceed rim manufacturer's limits without the consent of the component manufacturer.