



U.S. Canada Français Canadien

Truck & Bus Tires



Tires

▶ View Treads

▶ Tire Selector

Tire selector >

Emergency Road Service

Load/Inflation & Technical Info

Brochures & Catalogs

Real ANSWERS Magazine

Tools for Longer Wear

More Web Sites

For the Press

Contact Us

Bridgestone Truck Tires

R250F

Rugged regional/urban steer/all-position

Ideal application:
Local - P&D Service



Warranty information
View Bridgestone Truck Tire Limited Warranty

Compares to:
Goodyear G169, G149, G661, G662 Michelin
XZE, XZE2+, XZE2, XZE*

Specially designed for regional line haul, P&D, over-the highway refuse and construction service.

Five ribs with four wide, straight grooves for precise handling and excellent traction.

Tough tread cap compound and solid shoulder ribs to resist maneuvering

scrub.

Protector ribs on both sidewalls to fight damage from curbing, cuts and abrasions.

Available sizes and technical data

Tire Size	Article Number	Load Rng.	Ply Rating	Meas. Rim	Tread Depth	Weight	Overall Diameter	Overall Width	Overall Width [loaded]	Static Loaded Radius	Revs Per Mile	Load Limit Single	Load Limit Dual	Max. Speed
					32nds/mm	lbs/kg	in/mm	in/mm	in/mm	in/mm	rpm/rpk	lbs@psi/kg@kpa		mph/kph
215/75R17.5	199867	G	14	6.0	16	61.5	30.5	8.5	9.3	14.3	681.0	3750@100	3525@100	75
					metric: 13	27.9	775	216	236	363	423	1700@690	1600@690	120
225/70R19.5	153028	F	12	6.0	14	63.3	32.2	8.5	9.4	15.0	645.0	3640@95	3415@95	75
					metric: 11	28.7	818	216	239	381	401	1650@660	1550@660	120
245/70R19.5	299898	F	12	6.75	19	77.2	33.4	9.4	10.3	15.5	622.0	4080@95	3860@95	75
					metric: 15	35.0	848	239	262	394	386	1850@660	1750@660	120
245/70R19.5	227261	G	14	6.75	19	77.2	33.4	9.4	10.3	15.5	622.0	4540@110	4410@110	75
					metric: 15	35.0	848	239	262	394	386	2060@760	2000@760	120
245/70R19.5	227295	H	16	6.75	19	77.3	33.4	9.4	10.3	15.5	621.0	4940@120	4675@120	75
					metric: 15	35.1	848	239	262	394	386	2240@830	2120@830	120
265/70R19.5	297518	G	14	7.5	16	84.0	34.3	10.0	11.0	15.9	606.0	5355@110	5070@110	75
					metric: 13	38.1	871	254	279	404	377	2430@760	2300@760	120
9R22.5	292885	F	12	6.75	17	83.1	38.3	8.9	9.7	18.0	542.0	4540@105	4300@105	75
					metric: 13	37.7	973	226	246	457	337	2060@720	1950@720	120
10R22.5	292680	F	12	7.5	18	100.7	40.0	9.8	10.7	18.7	519.0	5205@100	4940@100	75
					metric: 14	45.7	1016	249	272	475	322	2360@690	2240@690	120
10R22.5	292729	G	14	7.5	18	101.1	40.0	9.8	10.7	18.7	519.0	5675@115	5355@115	75
					metric: 14	45.9	1016	249	272	475	322	2575@790	2430@790	120
11R22.5	290661	G	14	8.25	19	117.6	41.3	10.8	11.8	19.3	503.0	6175@105	5840@105	75
					metric: 15	53.3	1049	274	300	490	313	2800@720	2650@720	120
12R22.5	292850	H	16	9.0	20	135.4	42.7	11.6	12.6	19.8	487.0	7390@120	6780@120	75
					metric: 16	61.4	1085	295	320	503	303	3350@830	3075@830	120

245/75R22.5	292869	G	14	6.75	18	92.8	37.4	9.6	10.5	17.6	555.0	4675@110	4300@100	75
				metric:	14	42.1	950	244	267	447	345	2120@760	1950@690	120
265/75R22.5	292877	G	14	7.5	18	97.2	38.4	10.2	11.1	18.0	541.0	5205@110	4805@100	75
				metric:	14	44.1	975	259	282	457	336	2360@760	2180@690	120
295/75R22.5	289086	G	14	8.25	19	111.0	40.2	11.2	12.2	18.8	517.0	6175@110	5675@110	75
				metric:	15	50.3	1021	284	310	478	321	2800@760	2575@760	120
295/80R22.5	292834	H	16	9.0	19	128.9	41.6	11.7	12.7	19.4	499.0	7830@125	6940@125	75
				metric:	15	58.5	1057	297	323	493	310	3550@860	3150@860	120
11R24.5	290696	G	14	8.25	19	125.4	43.3	10.8	11.8	20.3	480.0	6610@105	6005@105	75
				metric:	15	56.9	1100	274	300	516	298	3000@720	2725@720	120
285/75R24.5	290726	G	14	8.25	19	118.9	41.4	10.6	11.6	19.4	502.0	6175@110	5675@110	75
				metric:	15	53.9	1052	269	295	493	312	2800@760	2575@760	120

Date: 06/16/2010

© 2006-2010 Bridgestone Americas Tire Operations, LLC. | legal notice