



DUNLOP® TIRES — FIND THE RIGHT TIRE



FIND THE RIGHT TIRE | TIRE SPECIFICATIONS

SIGNATURE

Premium Touring Ride With A Performance Attitude

FEATURES	BENEFITS
Tread Life Limited Mileage Warranty	Confidence in your purchase decision.
T rated 75,000 mile or H/V rated 60,000 miles	Consistent handling, ride comfort and tread wear in a wide range of load conditions.
VersaLoad™Technology	Help provide a tighter rim/wheel fit for superb handling and ride comfort.
Elliptical Sidewall Rings and Constant Gauge Chafer	Helps maintain the tire's shape for smooth performance and ride at highway speeds while delivering longer wear.
Jointless Band Technology™	Stays in constant contact with the road for consistent wheel response and driving feedback.
Stability Rib	Helps deliver responsive dry handling, effective water evacuation, even wear, noise reduction and confident all-season capability.
Highly detailed tread pattern including Multi-Pitch Tread Design Technology™and Evaqua™ Grooves	Helps maintain tire uniformity for a smooth, comfortable ride.
Dimensionally Stable Polyester Technology™	

<i>Tire Size</i>	<i>Service Descrip.</i>	<i>Sidewall</i>	<i>Approved Rim Width</i>	<i>Measured Rim Width</i>	<i>Section Width</i>	<i>Outside Diameter</i>	<i>Tread Width</i>	<i>Max. Load</i>
P205/60R16	<u>91T</u>	BSW	5.5 - 7.5	6.00	8.2	25.7		1,356 @ 44

215/65R16	<u>98T</u>	BSW	6.0 - 7.5	6.50	8.7	27.0	1,653 @ 44
P205/70R15	<u>95T</u>	BSW	5.0 - 7.0	6.00	8.3	26.4	1,499 @ 44
225/60R16	<u>98H</u>	BSW	6.0 - 8.0	6.50	9.0	26.6	1,653 @ 44
P215/60R16	<u>94V</u>	BSW	6.0 - 7.5	6.50	8.7	26.2	1,477 @ 44
P185/65R15	<u>86H</u>	BSW	5.0 - 6.5	5.50	7.5	24.5	1,168 @ 44
P205/55R16	<u>89T</u>	BSW	5.5 - 7.5	6.50	8.4	24.9	1,279 @ 44
P225/55R17	<u>95V</u>	BSW	6.0 - 8.0	7.00	9.2	26.8	1,521 @ 44
225/60R16	<u>98T</u>	BSW	6.0 - 8.0	6.50	9.0	26.6	1,653 @ 44
P215/60R16	<u>94T</u>	BSW	6.0 - 7.5	6.50	8.7	26.2	1,477 @ 44
P205/65R15	<u>92T</u>	BSW	5.5 - 7.5	6.00	8.3	25.5	1,400 @ 44
P195/60R15	<u>87T</u>	BSW	5.5 - 7.0	6.00	7.9	24.2	1,190 @ 44
205/65R15	<u>94H</u>	BSW	5.5 - 7.5	6.00	8.3	25.5	1,477 @ 44
P185/60R15	<u>84T</u>	BSW	5.0 - 6.5	5.50	7.5	23.8	1,102 @ 44
P195/60R15	<u>87H</u>	BSW	5.5 - 7.0	6.00	7.9	24.2	1,190 @ 44
P195/65R15	<u>89T</u>	BSW	5.5 - 7.0	6.00	7.9	25.0	1,279 @ 44
							1,356 @

205/55R16	<u>91H</u>	BSW	5.5 - 7.5	6.50	8.4	24.9	44
P205/60R15	<u>90H</u>	BSW	5.5 - 7.5	6.00	8.2	24.7	1,301 @ 44
P215/60R15	<u>93T</u>	BSW	6.0 - 7.5	6.50	8.7	25.2	1,411 @ 44
P205/60R16	<u>91H</u>	BSW	5.5 - 7.5	6.00	8.2	25.7	1,356 @ 44
P175/65R14	<u>81T</u>	BSW	5.0 - 6.0	5.00	7.0	23.0	1,019 @ 44
P215/55R16	<u>91H</u>	BSW	6.0 - 7.5	7.00	8.9	25.3	1,356 @ 44
P205/65R16	<u>94T</u>	BSW	5.5 - 7.5	6.00	8.2	26.5	1,477 @ 44
P225/55R17	<u>95T</u>	BSW	6.0 - 8.0	7.00	9.2	26.8	1,521 @ 44
P215/60R15	<u>93H</u>	BSW	6.0 - 7.5	6.50	8.7	25.2	1,411 @ 44
195/65R15	<u>91H</u>	BSW	5.5 - 7.0	6.00	7.9	25.0	1,356 @ 44
P215/70R15	<u>97T</u>	BSW	5.5 - 7.0	6.50	8.7	26.9	1,620 @ 44
P185/65R14	<u>85T</u>	BSW	5.0 - 6.5	5.50	7.5	23.5	1,124 @ 44