

High Country All Terrain

Sizes and Specifications

Size	UTQG	Load / Speed	Load / Ply	Item #	Meas. Rim	Approved Rims	OD	Section Width	RPM	Tread Width	Tread Depth	Weight (lbs)*	Max PSI (cold)	Max Load	Reinforced	Sidewall
LT30X9.50R15		104S	C/6	28210312	7.5	6.5 - 8.5	29.5	9.7	715	7.4	16/32	36	50	1985		OWL
LT31X10.50R15		109S	C/6	28210322	8.5	7.0 - 9.0	30.5	10.9	693	8.3	17/32	42	50	2270		OWL
P215/75R15	500-A-B	100S		28210527	6	5.5 - 7.0	27.7	8.3	764	6.6	13/32	30	44	1742		OWL
P225/75R15	500-A-B	102S		28210528	6	6.0 - 7.5	28.3	8.8	747	6.9	13/32	31	44	1874		OWL
P235/70R15	500-A-B	102S		28210517	7	6.0 - 8.0	27.9	9.4	757	7.3	13/32	31	44	1896		OWL
LT235/75R15		104/101S	C/6	28210511	6.5	6.0 - 7.0	28.8	9.1	751	7.2	16/32	35	50	1985		OWL
P235/75R15	500-A-B	105S		28210529	6.5	6.0 - 8.0	28.8	9.2	736	7.3	13/32	35	44	2028		OWL
P265/70R15	500-A-B	110S		28210506	8	7.0 - 9.0	29.7	10.7	715	8.3	13/32	37	44	2337		BLT
P265/75R15	500-A-B	112S		28210515	7.5	7.0 - 9.0	31	10.4	686	8.3	13/32	44	44	2469		OWL
P215/70R16	500-A-B	99S		28210603	6.5	5.5 - 7.0	27.8	8.7	758	6.6	13/32	28	44	1709		BLT
LT215/85R16		115/112Q	E/10	28216464	6	5.5 - 7.0	30.4	8.5	710	6	16/32	39	80	2680		BLT
P225/70R16	500-A-B	101T		28214693	6.5	6.0 - 7.5	28.5	9	742	6.9	13/32	34	44	1819		OWL
LT225/75R16		115/112Q	E/10	28216482	6	6.0 - 7.0	29.4	8.4	733	6.9	16/32	40	80	2680		BLT
P225/75R16	500-A-B	104S		28210484	6	6.0 - 7.5	29.3	8.9	721	6.9	13/32	33	44	1984		BLT
P235/70R16	500-A-B	104T		28214609	7	6.0 - 8.0	28.9	9.6	730	7.3	13/32	32	44	1984		OWL
LT235/85R16		120/116Q	E/10	28216474	6.5	6.0 - 7.5	31.7	9.3	683	6.7	16/32	50	80	3042		BLT
P245/70R16	500-A-B	106T		28214604	7	6.5 - 8.0	29.5	9.6	717	7.7	13/32	38	44	2094		OWL
LT245/75R16		108/104S	C/6	28210492	7	6.5 - 8.0	30.5	9.7	709	7.6	16/32	39	50	2205		OWL
LT245/75R16		120/116Q	E/10	28216494	7	7.0 - 8.0	30.5	9.7	710	7.6	16/32	51	80	3042		OWL
P245/75R16	500-A-B	109S		28210608	7	6.5 - 8.0	30.5	9.6	695	7.7	13/32	37	44	2271		OWL
255/65R16	500-A-B	109H		28211602	7.5	7.0 - 9.0	29.5	9.8	724	7.7	13/32	37	51	2271		BLT
P255/70R16	500-A-B	109T		28214605	7.5	6.5 - 8.5	31.1	10.2	701	8	13/32	41	44	2271		OWL
P265/70R16	500-A-B	111T		28214606	8	7.0 - 9.0	30.6	10.6	695	8.3	13/32	42	44	2403		OWL
LT265/75R16		112/109S	C/6	28210502	7.5	7.0 - 8.0	31.6	10.5	686	8.3	17/32	49	50	2470		OWL
LT265/75R16		123/120Q	E/10	28216504	7.5	7.0 - 8.0	31.7	10.5	684	8.3	17/32	55	80	3415		OWL
P265/75R16	500-A-B	114S		28210503	7.5	7.0 - 9.0	31.6	10.4	671	8.3	13/32	42	44	2601		OWL
P275/70R16	500-A-B	114T		28214607	8	7.0 - 9.0	31.1	11	681	8.6	14/32	43	44	2601		BLT
LT285/75R16		122/119Q	D/8	28216611	8	7.5 - 9.0	32.5	11	668	8.7	17/32	52	65	3305		OWL
235/65R17	500-A-B	104T		28211790	7	6.5 - 8.5	28.9	9.3	733	7.3	13/32	36	51	1984		OWL
LT265/70R17		121/118S	E/10	28210702	8	7.0 - 8.5	31.7	10.7	681	8.3	17/32	56	80	3195		OWL

P265/70R17	500-A-B	113S		28210701	8	7.0 - 9.0	31.6	10.7	668	8.3	13/32	43	44	2535		OWL
LT285/70R17		121/118S	D/8	28210612	8.5	7.5 - 9.0	32.9	11.4	658	8.9	17/32	61	65	3195		OWL
285/60R18	500-A-B	120H		28211856	8.5	8.0 - 10.0	31.6	11.3	673	8.9	13/32	43	50	3086	RF	BLT
305/50R20	500-A-B	120H		28211015	9.5	8.5 - 11.0	32	12.3	661	10.2	14/32	48	50	3086	RF	BLT

*Tread design, technical information and tire construction subject to change without notice and may vary by size.