

# WildPeak A/T

## Sizes and Specifications

Size	UTQG	Load / Speed	Load / Ply	Item #	Meas. Rim	Approved Rims	OD	Section Width	RPM	Tread Width	Tread Depth	Weight (lbs)*	Max PSI (cold)	Max Load	Reinforced	Sidewall
30X9.50R15		104S	C/6	28440512	7.5	6.0 - 8.5	29.6	9.7	714	7.5	16/32	39	50	1985		OWL
31X10.50R15		109S	C/6	28440514	8.5	7.0 - 9.0	30.5	10.7	692.8054424	8.3	17/32	43	50	2270		OWL
32X11.50R15		113S	C/6	28440510	9	8.0 - 10.0	31.5	11.6	671.490419	9.1	17/32	47	50	2535		OWL
33x12.50R15		108S	C/6	28440518	10	8.5 - 11.0	32.6	12.8	651.2217957	9.9	18/32	54	35	2205		BLK
LT225/75R16		110/107Q	D/8	28446627	6	6.0 - 7.0	29.4	8.7	709.1342128	7	15/32	39	65	2335		BLK
LT245/70R16		113/110Q	D/8	28446624	7	6.0 - 7.0	29.6	9.7	703.0716067	7.7	16/32	47	65	2235		OWL
LT245/75R16		120/116Q	E/10	28446628	7	6.5 - 8.0	30.6	9.7	682.7719949	7.6	16/32	54	80	3042		OWL
255/65R16	500-A-B	109S		28440642	7.5	7.0 - 9.0	29.1	10.2	732.6152095	8.1	13/32	38	44	2271		BLK
LT265/70R16		117/114Q	D/8	28446638	8	7.0 - 8.5	30.8	10.5	678.8184765	8.3	17/32	52	65	2835		OWL
LT265/75R16		123/120Q	E/10	28446639	7.5	7.0 - 8.0	31.7	10.6	659.0870158	8.3	17/32	56	80	3415		OWL
LT285/75R16		122/119Q	D/8	28446640	8	7.0 - 9.0	32.9	11.1	636.1077097	8.9	17/32	62	65	3305		OWL
LT305/70R16		124/121S	E/10	28440641	9	8.0 - 9.5	32.8	12.1	637.2848841	9.6	18/32	67	65	3525		BLK
33X12.50R17		114S	D/8	28440710	10	8.5 - 11.0	32.5	12.5	648	10.1	17/32	63	50	2600		BLK
245/65R17	500-A-B	107S		28440768	7	7.0 - 8.5	29.6	9.5	718.2792012	7.8	13/32	37	44	2149		OWL
LT245/70R17		119/116Q	E/10	28446718	7	6.0 - 8.0	30.7	9.5	678.223694	7.7	16/32	53	80	3000		BLK
LT245/75R17		121/118Q	E/10	28446711	7	6.0 - 7.5	31.5	9.7	661.8485845	7.6	16/32	54	80	3195		BLK
255/65R17	500-A-B	110S		28440713	7.5	7.0 - 9.0	30.2	10.1	705.9999093	8.1	13/32	40	44	2337		OWL
255/70R17	500-A-B	112S		28440769	7.5	6.5 - 8.5	31.1	10	678.6305851	8	13/32	41	44	2469		OWL
265/65R17	500-A-B	112S		28440721	8	7.5 - 9.5	30.6	10.6	696.1249798	8.4	13/32	41	44	2469		BLK
LT265/70R17		121/118S	E/10	28440712	8	7.0 - 8.5	31.8	10.3	655	8.3	17/32	54	80	3195		BLK
LT285/70R17		121/118S	D/8	28440719	8.5	7.0 - 9.5	32.8	11.3	636.6134878	9	17/32	61	65	3195		BLK
LT305/65R17		121/118S	E/10	28440720	9	8.5 - 11.0	32.6	12.1	643.4984405	9.7	17/32	64	65	3195		BLK
265/70R18	500-A-B	116S		28440809	8	7.0 - 9.0	32.6	10.8	647.8789033	8.3	13/32	51	44	2756		OWL
LT275/65R18		123/120Q	E/10	28446803	8	7.5 - 9.0	32.2	10.8	627.3511045	8.7	17/32	61	80	3415		OWL
LT285/65R18		121/118S	D/8	28440804	8.5	8.0 - 10.0	32.6	11.2	642.6010792	9.1	17/32	61	65	3195		OWL
275/60R20	500-A-B	115S		28440003	8	7.5 - 9.5	33.1	10.9	640.3973982	8.8	13/32	46	44	2679		BLK
285/50R20	500-A-B	116T		28444020	9	8.0 - 10.0	31.3	11.3	673.585031	9.3	13/32	46	50	2756	RF	BLK

\*Tread design, technical information and tire construction subject to change without notice and may vary by size.