

Firestone®

DESTINATION™ LE with UNI-T®

Firestone engineered the Destination LE to give light trucks and SUVs the advantage of UNI-T technology. The result is a tire that allows for command of the road with comfort. The Destination LE combines outstanding performance on wet and dry roads with the comfort and quiet of passenger tires. That makes for a relaxing ride on those long commutes. With a 60,000 mile limited treadwear warranty, the Destination LE with UNI-T is built to go the distance and give you plenty of time to enjoy the drive.

WARRANTY SUMMARY

60,000 MILE LIMITED TREADWEAR WARRANTY†
0 MILE LIMITED TREADWEAR WARRANTY†
GOLD PLEDGE LIMITED WARRANTY††
BUY & TRY 30 DAY GUARANTEE‡



†Prorated replacement if warranted mileage not attained; actual tread life may vary. Certain restrictions and limitations may apply. Ask your retailer for details.

††Replacement at no charge (excluding taxes and disposal fees) if your Firestone tire becomes unusable for any reason within the manufacturer's control for up to 3 years from date of purchase or 4 years from date of manufacture, whichever is to the owner's advantage. Certain restrictions and limitations may apply.

‡Original proof of purchase required to take advantage of the 30 Day Test Drive. Tires must be returned within 30 days of purchase. Does not apply to tires supplied as original equipment on new vehicles.



O-BEAD

Improves uniformity and ride comfort through use of a single continuous strand of cable in the bead construction

5§ NOISE REDUCTION

Produces noise-canceling sound waves to significantly reduce tire noise on road surfaces

Weathergrip

A tread compound that blends special polymers to promote traction on wet surfaces.

CO-CS (Computer Optimized Component System)

Maximizes tire performance by optimizing the appropriate combination of tread design, casing shape, materials, and construction.

LL CARBON (LONG LINK)

Helps improve tread wear and resist cracking, chipping and tearing through the use of a special long length carbon structure

Spiral Wrap

Provides a higher level of uniformity and high speed capability through use of a continuous nylon wrap

Destination LE with Uni-T**TIRE SPECIFICATIONS**

Size	Service Description	Load Range	Speed Rating	Sidewall Styling	Article Number	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Static Load Radius	Tread Depth (32")	RPM	Tire Weight	UTQG	Limited Mileage Warranty+
P265/65R18	112S		S	BL	090177	7.5-9.5	8.0	31.7	10.7	14.2	13	657	41		
P265/65R18	112S		S	OWL	090279	7.5-9.5	8.0	31.7	10.7	14.2	12	657	42		
P275/60R20	114S		S	OWL	108741	7.5-9.5	8.0	33.0	11.0	15.0	13	631	47	480 A B	60,000
P275/55R20	111H		H	BL	108775	7.5-9.5	8.5	31.9	11.2	14.6	11	653	45	480 A B	60,000
P235/65R18	104T		T	OWL	108792	6.5-8.5	7.0	30.0	9.5	13.6	12	694	34	480 A B	60,000
P265/60R20	106V		V	BL	108809	7.5-9.5	8.5	30.5	10.9	14.0	11	683	40	480 A B	60,000
P235/75R16	109S	XL	S	OWL	054358	6.0-7.5	6.5	29.8	9.3	13.3	12	699	36	480 AB	60,000
P215/75R15	100S		S	OWL	146914	5.5-7.0	6.0	27.7	8.5	12.4	12	752	27	480 A B	60,000
P225/75R15	102S		S	OWL	146931	6.0-7.5	6.0	28.3	8.8	12.6	12	736	30	480 A B	60,000
P235/75R15	105S		S	OWL	146965	6.0-8.0	6.5	28.9	9.3	12.8	12	721	32	480 A B	60,000
P265/75R15	112S		S	OWL	054341	7.0-9.0	7.5	30.6	10.5	13.5	13	679	39	480 A B	60,000
P225/75R16	106S	XL	S	BL	040860	6.5-8.0	7.0	30.5	8.8	13.1	12	0	33	480 A B	60,000
P245/75R16	109S		S	OWL	147016	6.5-8.0	7.0	30.5	9.8	13.5	13	683	38	480 A B	60,000
P265/75R16	114S		S	OWL	147050	7.0-9.0	7.5	31.7	10.5	14.0	13	657	43	480 A B	60,000
P225/70R14	98S		S	OWL	147543	6.0-7.5	6.5	26.5	9.0	11.8	12	786	27	480 A B	60,000
* P215/70R15	97S		S	BL	030439	5.5-7.0	6.5	26.9	8.7	12.1	12	774	23	480 A B	60,000
P225/70R15	100S		S	OWL	146948	6.0-7.5	6.5	27.4	9.0	12.3	12	760	29	480 A B	60,000
P235/70R15	102S		S	OWL	146982	6.0-8.0	7.0	28.0	9.5	12.5	12	744	31	480 A B	60,000
P255/70R15	108S		S	OWL	146829	6.5-8.5	7.5	29.1	10.2	12.9	13	716	34	480 A B	60,000
P225/70R16	101S		S	OWL	147560	6.0-7.5	6.5	28.4	9.0	12.8	12	733	31	480 A B	60,000
P215/70R16	99S		S	BL	083224	5.5-7.0	6.5	27.9	8.7	12.6	12	748	28	480 A B	60,000
P245/70R16	106S		S	OWL	123838	6.5-8.0	7.0	29.5	9.8	13.2	13	706	36	480 A B	60,000
P255/70R16	109S		S	OWL	147033	6.5-8.5	7.5	30.1	10.2	13.4	13	692	37	480 A B	60,000
P265/70R16	111S		S	OWL	123846	7.0-9.0	8.0	30.6	10.7	13.6	13	681	40	480 A B	60,000
P265/70R17	113S		S	OWL	147067	7.0-9.0	8.0	31.7	10.7	14.1	13	657	43	480 A B	60,000
P265/70R18	114S		S	OWL	066173	7.0-9.0	8.0	32.6	10.7	14.6	13	639	44	480 A B	60,000
P245/70R17	108S		S	OWL	087389	6.5-8.0	7.0	30.6	9.8	13.7	13	673	37	480 A B	60,000
P255/65R16	106S		S	OWL	040877	7.0-9.0	7.5	29.1	10.2	13.0	13	0	35	480 A B	60,000
P235/65R17	103T		T	BL	040911	6.5-8.5	7.0	29.1	9.5	13.1	13	0	31	480 A B	60,000
225/65R17	102S		S	BL	083173	6.0-8.0	6.5	28.4	9.0	12.9	13	733	31	480 A B	60,000
P255/65R17	108S		S	OWL	083190	7.0-9.0	7.5	30.2	10.2	13.5	13	690	39	480 A B	60,000
P245/65R17	105S		S	OWL	040928	7.0-8.5	7.0	29.5	9.8	13.3	13	0	35	480 A B	60,000
P265/65R17	110T		T	BL	054392	7.5-9.5	8.0	30.6	10.7	13.7	13	681	37	480 A B	60,000
P275/60R17	110S		S	BL	040945	7.5-9.5	8.0	30.0	11.0	13.5	13	0	39	480 A B	60,000
P265/60R18	109T		T	OWL	054409	7.5-9.5	8.0	30.6	10.7	13.8	11	683	39	480 A B	60,000
31X10.50R15LT	109R	C	R	OWL	158404	7.0-9.0	8.5	30.5	10.5	14.1	15	683	41	0	
LT235/75R15	104S	C	S	OWL	158438	6.0-7.0	6.5	28.9	9.3	13.4	14	721	36	0	
LT265/75R16	112S	C	S	OWL	158710	7.0-8.0	7.5	31.7	10.5	14.7	15	657	45	0	
P235/60R17	100H		H	BL	112379	6.5-8.5	7.0	28.3	9.5	12.8	10	736	30	480 A B	60,000
P235/70R17	108S	XL	S	OWL	097538	6.0-8.0	7.0	30.0	9.5	13.5	12	694	36	480 A B	60,000

All LT and flotation sizes are excluded from the 60k warranty.

†Prorated replacement if warranted mileage not attained; actual tread life may vary. Certain restrictions and limitations may apply. Ask your retailer for details.

