

## **TRANSFORCE** HT

The Transforce HT is packed with features to make it a driving force for light truck and commercial vehicles. UNI-T technology along with deep shoulder slots and circumferential grooves gives traction in wet conditions. The polyester and steel construction plus a high modulus tread compound help resist the rigors of heavy-duty work. With a modern, all-season tread design and noise reduction technology, the Transforce HT also provides a comfortable ride.

## **WARRANTY SUMMARY**

0 MILE LIMITED TREADWEAR WARRANTY†
GOLD PLEDGE LIMITED WARRANTY††
BUY & TRY 30 DAY GUARANTEE‡



†Prorated replacement if warranted mileage not attained; actual tread life my vary. Certain restrictions and limitations may apply. Ask your retailer for details. ††Replacement at no charge (excluding taxes and disposal fees) if your Firestone tire becomes unusable for any reason within the manufacturer's control for up to 3 years from date of purchase or 4 years from date of manufacture, whichever is to the owner's advantage. Certain restrictions and limitations may apply. ‡Original proof of purchase required to take advantage of the 30 Day Test Drive. Tires must be returned within 30 days of purchase. Does not apply to tires supplied as original equipment on pew vehicles.



Computer-Designed Shape and Body Contributes to ride comfort

Continuous Shoulder Ribs Helps increase tread life

Advanced High Modulus Tread Compound and Polyester and Steel Construction Helps to prevent damage and promotes long wear

Circumferential Grooves
Promotes extra traction in wet conditions

5 degree Noise Reduction Reduces noise on road surfaces

## **Transforce HT with Uni-T**

## **TIRE SPECIFICATIONS**

Size	Service Description	Load Range	Speed Rating	Sidewall Styling	Article Number	Approved Rim Widths	Measuring Rim Widths	Overall Tire Diameter	Overall Section Width	Static Load Radius	Tread Depth (32")	RPM	Tire Weight	UTQG	Limited Mileage Warranty+
** LT215/85R16	115R	E	R	BL	189701	5.5-7.0	6.0	30.4	8.5	14.1	14	686	35	0	
* LT235/85R16	120R	E	R	BL	189718	6.0-7.5	6.5	31.7	9.3	14.7	15	657	40		
* LT225/75R16	115R	E	R	BL	189752	6.0-7.0	6.0	29.3	8.8	13.6	14	712	35		
* LT245/75R16	120R	E	R	BL	189769	6.5-8.0	6.5	30.5	9.8	14.1	14	684	39		
* LT265/75R16	123R	E	R	BL	189786	7.0-8.0	7.5	31.7	10.5	14.7	15	659	44		
LT265/75R16	123R	E	R	OWL	207602	7.0-8.0	7.5	31.7	10.5	14.7	15	659	44		
* 8.75R16.5LT	115R	E	R	BL	189803	6.0-6.8	6.8	29.5	8.8	13.8	14	708	35		
* 9.50R16.5LT	121R	E	R	BL	189820	6.8-8.2	6.8	30.6	9.5	14.2	15	682	40		
* LT235/75R15	104R	С	R	BL	189837	6.0-7.0	6.5	28.9	9.3	13.4	15	723	32		
* LT235/80R17	120R	E	R	BL	191282	6.0-7.5	6.5	31.8	9.3	14.8	15	656	41		
* LT245/70R17	119R	E	R	BL	191316	6.5-8.0	7.0	30.6	9.8	14.3	14	683	41		
LT265/70R17	121R	E	R	OWL	200156	7.0-8.5	8.0	31.7	10.7	14.7	14	657	46		
LT245/75R17	121R	E	R	OWL	207483	6.5-7.5	7.0	31.5	9.8	14.7	14	661	42	0	
LT275/70R18	125R	E	R	OWL	207500	0.0-0.0	0.0	0.0	11.0	15.5	16	628	50	0	
LT275/65R18	123S	E	S	OWL	207619	7.5-9.0	8.0	32.1	11.0	15.0	15	651	50		
LT225/75R17	116R	E	R	BL	224133	6.0-7.5	6.0	30.3	8.8	14.2	14	687	37		

\*Gold Pledge 3 Year Limited Warranty and 30 Day Test Drive on consumer applications only, commercial applications excluded.
†Prorated replacement if warranted mileage not attained; actual tread life my vary. Certain restrictions and limitations may apply. Ask your retailer for details.



