



## EAGLE LS-2

All-Season Traction And A Smooth,  
Quiet Ride



### Features & Benefits

Wide Circumferential Grooves Help Efficiently  
Evacuate Water From Beneath The Tread

Special Tread Block Sequence Helps Enhance  
Handling And Traction And Reduces Tread Noise

Premium Sidewall Styling Gives A Contemporary  
Appearance

### Tire Ratings

What do these ratings mean?

Dry Traction	Wet Traction	Snow Traction	Ride Comfort	Quiet Ride
7	7	7	10	10

### Tire Sizes

Tire Size	Service Description	Sidewall	Approved Rim Width (inches)	Meas. Rim (inches)	Section Width (inches)	Outside Diameter (inches)	Tread Depth (32nds of inch)	Max Load (lbs)
205/50R17	89H	BSW	5.5 - 7.5	6.50	8.4	25.1	12/32	1,279 @ 51
215/55R16	97H	VSB	6.0 - 7.5	7.00	8.9	25.3	11/32	1,609 @ 50
215/65R16	98H	BLT	6.0 - 7.5	6.50	8.7	27.0	10/32	1,653 @ 51
225/50R17	94H	BLT	6.0 - 8.0	7.00	9.2	25.9	12/32	1,477 @ 51
225/50R17	94H	BLT	6.0 - 8.0	7.00	9.2	25.9	10/32	1,477 @ 51
225/55R17	97V	BLT	6.0 - 8.0	7.00	9.2	26.8	10/32	1,609 @ 51
235/45R17	97H	VSB	7.5 - 9.0	8.00	9.3	25.4	10/32	1,609 @ 50
235/55R18	104H	BLT	6.5 - 8.5	7.50	9.7	28.2	10/32	1,984 @ 50
235/55R19	101H	BLT	8.5 - 6.5	7.50	9.7	29.2	10/32	1,819 @ 51
245/40R18	93H	BLT	8.0 - 9.5	8.50	9.8	25.7	10/32	1,433 @ 51
245/40R19	98V	BLT	8.0 - 9.5	8.50	9.8	26.7	10/32	1,653 @ 50
245/45R17	95H	BLT	7.5 - 9.0	8.00	9.6	25.7	10/32	1,521 @ 51
245/45R17	95H	BLT	7.5 - 9.0	8.00	9.6	25.7	10/32	1,521 @ 51
245/45R18	100V	BLT	7.5 - 9.0	8.00	9.6	26.7	10/32	1,764 @ 50
245/45R19	102V	BLT	7.5 - 9.0	8.00	9.6	27.7	10/32	1,874 @ 50
245/50R18	100W	BLT	7.0 - 8.5	7.50	10.0	27.7	10/32	1,764 @ 51
245/50R18	100V	BLT	7.0 - 8.5	7.50	10.0	27.7	10/32	1,764 @ 51
255/40R19	100H	BLT	8.5 - 10.2	9.00	10.2	27.0	11/32	1,764 @ 50
255/45R18	99H	BLT	8.0 - 9.5	8.50	10.0	27.0	11/32	1,709 @ 51
255/45R19	100V	BLT	8.0 - 9.5	8.50	10.0	28.1	10/32	1,764 @ 51
255/55R18	109H	BLT	7.0 - 9.0	8.00	10.4	29.0	10/32	2,271 @ 50
255/55R18	109V	BLT	7.0 - 9.0	8.00	10.4	29.0	10/32	2,271 @ 50
255/55R18	109V	BLT	7.0 - 9.0	8.00	10.4	29.0	10/32	2,271 @ 50
255/55R18	109H	BLT	7.0 - 9.0	8.00	10.4	29.0	10/32	2,271 @ 50
265/50R19	110V	BLT	7.5 - 9.5	8.50	10.9	29.5	10/32	2,337 @ 50

265/50R19	110H	VSB	7.5 - 9.5	8.50	10.9	29.5	10/32	2,337 @ 50
265/50R19	110H	BLT	7.5 - 9.5	8.50	10.9	29.5	10/32	1,060 @ 50
275/45R19	108V	BLT	8.5 - 10.5	9.00	10.7	28.8	10/32	2,205 @ 50
275/45R20	110H	BLT	8.5 - 10.5	9.00	10.7	29.8	10/32	2,337 @ 50
275/45R20	110H	B01	8.5 - 10.5	9.00	10.7	29.8	10/32	2,337 @ 50
275/45R20	110V	BLT	8.5 - 10.5	9.00	10.7	29.8	10/32	1,060 @ 50
275/50R20	109H	VSB	7.5 - 9.5	8.50	11.2	30.9	10/32	2,270 @ 51
285/40R19	103V	BLT	9.5 - 11.0	10.00	11.4	28.0	10/32	1,929 @ 51
P195/65R15	89S	VSB	5.5 - 7.0	6.00	7.9	25.2	9/32	1,279 @ 51
P205/70R16	96T	VSB	5.0 - 7.0	6.00	8.2	27.3	11/32	1,565 @ 44
P215/45R17	87H	VSB	7.0 - 8.0	7.00	8.4	24.7	10/32	1,201 @ 51
P215/50R17	90V	VSB	6.0 - 7.5	7.00	8.9	25.5	10/32	1,323 @ 51
P225/50R18	94T	B01	6.0 - 8.0	7.00	9.2	26.9	11/32	1,477 @ 44
P225/55R17	95T	B01	6.0 - 8.0	7.00	9.2	26.8	10/32	1,521 @ 44
P225/55R18	97H	B01	6.0 - 8.0	7.00	9.2	27.8	10/32	1,609 @ 44
P225/55R18	97H	VSB	6.0 - 8.0	7.00	9.2	27.8	10/32	1,609 @ 44
P225/65R16	99H	VSB	6.0 - 8.0	6.50	9.0	27.5	10/32	1,709 @ 44
P255/55R18	104H	VSB	7.0 - 9.0	8.00	10.4	29.0	11/32	1,984 @ 44
P275/55R20	111S	B02	7.5 - 9.5	8.50	11.2	31.9	11/32	2,403 @ 44