



## WRANGLER MT/R WITH KEVLAR

The Revolutionary Off-Road Tire Built With The Rugged Toughness of DuPont™ Kevlar® for Enhanced Sidewall Puncture Resistance



### Features & Benefits

DuPont™ Kevlar® Reinforced Sidewalls Help Increase Sidewall Puncture Resistance By 35%\*

Hardworking Wraparound Tread Helps to Deliver Sidewall Traction In Deep Mud, Sand, And Rocks

Innovative Asymmetric Tread Design Helps Provide Aggressive Off-Road Traction And Enhanced Handling On The Road

Advanced Silica Rubber For Superb Off-Road And Wet Traction

\* Source: Goodyear Sidewall Penetration Energy - LT285/70R17 LR-D-65 psi.

DuPont™ and Kevlar® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company

### Tire Ratings

What do these ratings mean?

Dry Traction	Wet Traction	Snow Traction	Off-Road Traction	Quiet Ride
8	7	7	5	5

### Tire Sizes

Tire Size	Service Description	Sidewall	Approved Rim Width (inches)	Meas. Rim (inches)	Section Width (inches)	Outside Diameter (inches)	Max Load (lbs)
31X10.50R15LT	109Q	OWL	7.0 - 9.0	8.50	10.6	30.8	2,270 @ 50
32X11.50R15LT	113Q	OWL	8.0 - 10.0	9.00	11.4	31.8	2,535 @ 50
33X12.50R15LT	108Q	BSL	0.0 - 0.0	0.00	0.0	0.0	2,205 @ 35
33X12.50R15LT	108Q	OWL	8.5 - 11.0	10.00	12.5	32.8	2,205 @ 35
33X12.50R20LT	114Q	BSL	8.5 - 11.0	10.00	12.5	32.8	2,600 @ 65
35X12.50R15LT	113Q	BSL	8.5 - 11.0	10.00	12.5	34.8	2,535 @ 35
35X12.50R17LT	111Q	BSL	8.5 - 11.0	10.00	12.5	34.8	2,405 @ 35
35X12.50R18LT	123Q	BSL	8.5 - 11.0	10.00	12.5	34.8	3,415 @ 65
35X12.50R20LT	121Q	BSL	8.5 - 11.0	10.00	12.5	34.8	3,195 @ 65
37X12.50R17LT	124Q	BSL	8.5 - 11.0	10.00	12.5	36.8	3,525 @ 50
38X14.50R17LT	121Q	BSL	10.0 - 12.0	12.00	14.7	37.8	3,195 @ 50
40X13.50R17LT	121Q	BSL	8.5 - 11.0	11.00	13.6	39.8	3,195 @ 35
42X14.50R17LT	121Q	BSL	10.0 - 12.0	12.00	14.7	41.8	3,195 @ 35
LT235/85R16	120Q	BSL	6.0 - 7.5	6.50	9.3	31.7	3,042 @ 80
LT245/70R17	119Q	OWL	6.5 - 8.0	7.00	9.8	30.6	3,000 @ 80
LT245/70R17	108Q	OWL	6.5 - 8.0	7.00	9.8	30.6	2,205 @ 50
LT245/75R16	120Q	OWL	6.5 - 8.0	7.00	9.8	30.7	3,042 @ 80
LT245/75R17	121Q	OWL	6.5 - 7.5	7.00	9.8	31.7	3,195 @ 80
LT255/75R17	111Q	BSL	6.5 - 8.5	7.00	10.0	32.3	2,405 @ 50

LT265/70R17	121Q	OWL	7.0 - 8.5	8.00	10.7	31.7	3,195 @ 80
LT265/70R17	112Q	OWL	7.0 - 8.5	8.00	10.7	31.7	2,470 @ 50
LT265/75R16	123Q	OWL	7.0 - 8.0	7.50	10.5	31.7	3,415 @ 80
LT275/65R18	113Q	OWL	7.5 - 9.0	8.00	11.0	32.1	2,535 @ 50
LT275/65R20	126Q	BSL	7.5 - 9.5	8.00	11.0	34.1	3,750 @ 80
LT275/70R17	121Q	OWL	7.0 - 8.5	8.00	11.0	32.4	3,195 @ 80
LT275/70R18	125Q	OWL	7.0 - 8.5	8.00	11.0	33.4	3,640 @ 80
LT285/65R20	127Q	BSL	8.0 - 10.0	8.50	11.5	34.8	3,860 @ 80
LT285/70R17	121Q	OWL	7.5 - 9.0	8.50	11.5	33.0	3,195 @ 65
LT285/70R17	121Q	BSL	0.0 - 0.0	0.00	0.0	0.0	3,195 @ 65
LT285/75R16	126Q	OWL	7.5 - 9.0	8.00	11.3	33.1	3,750 @ 80
LT285/75R16	126Q	BSL	0.0 - 0.0	0.00	0.0	0.0	3,750 @ 80
LT285/75R18	129Q	BSL	7.5 - 9.5	8.00	11.3	35.1	4,080 @ 80
LT305/70R16	124Q	OWL	8.0 - 9.5	9.00	12.2	33.1	3,525 @ 65
LT305/70R17	119Q	OWL	8.0 - 9.5	9.00	12.2	34.1	3,000 @ 50
LT315/70R17	121Q	OWL	8.5 - 10.0	9.50	12.7	34.7	3,195 @ 50
LT315/75R16	121Q	BSL	8.0 - 10.0	8.50	12.3	34.8	3,195 @ 50