



WRANGLER SR-A

WetTrac® Technology For Confident Wet Traction, All-Terrain Capabilities And A Quiet Ride



Features & Benefits

Zig Zag Microgrooves Offer Enhanced Traction In Rain, Snow And Ice

Dual Circumferential Grooves Help Evacuate Water For Enhanced Wet Traction

Exclusive Wet Traction Compound Helps Provide Traction On Wet Roads

Tire Ratings

What do these ratings mean?

Dry Traction	Wet Traction	Snow Traction	Off-Road Traction	Quiet Ride
7	7	7	7	7

Warranty

50,000 Mile/80,000 Kilometer Tread Life Limited Warranty.

*P-Metric Sizes Only

*For complete details, download a PDF of the Limited Warranty Brochure or see a Sales Associate.

Tire Sizes

Tire Size	Service Description	Sidewall	Approved Rim Width (inches)	Meas. Rim (inches)	Section Width (inches)	Outside Diameter (inches)	Max Load (lbs)
215/70R16	100S	VSB	5.5 - 7.0	6.50	8.7	27.9	1,764 @ 51
225/70R16	103T	OWL	6.0 - 7.5	6.50	9.0	28.4	1,819 @ 51
245/60R18	105T	VSB	7.0 - 8.5	7.00	10.0	29.6	2,039 @ 51
31X10.50R15LT	109R	OWL	7.0 - 9.0	8.50	10.6	30.5	2,270 @ 50
LT215/85R16	115P	BSL	5.5 - 7.0	6.00	8.6	30.5	2,680 @ 80
LT225/75R16	115R	BSL	6.0 - 7.0	6.00	8.8	29.3	2,680 @ 80
LT235/80R17	120R	VSB	6.0 - 7.5	6.50	9.3	31.8	3,085 @ 80
LT235/85R16	120R	BSL	6.0 - 7.5	6.50	9.3	31.7	3,042 @ 80
LT245/70R17	119R	OWL	6.5 - 8.0	7.00	9.8	30.6	3,000 @ 80
LT245/75R16	120R	BSL	6.5 - 8.0	7.00	9.8	30.5	3,042 @ 80
LT245/75R16	120R	OWL	6.5 - 8.0	7.00	9.8	30.5	3,042 @ 80
LT245/75R17	121R	OWL	6.5 - 7.5	7.00	9.8	31.5	3,195 @ 80
LT265/60R20	121S	VSB	7.5 - 9.5	8.00	10.7	32.5	3,195 @ 80
LT265/70R17	121R	OWL	7.0 - 8.5	8.00	10.7	31.7	3,195 @ 80
LT265/70R17	121S	BSL	7.0 - 8.5	8.00	10.7	31.7	3,195 @ 80
LT265/70R18	124S	VSB	7.0 - 9.0	8.00	10.7	32.6	3,525 @ 80
LT265/75R16	123R	OWL	7.0 - 8.0	7.50	10.5	31.7	3,415 @ 80
LT275/65R18	123Q	OWL	7.5 - 9.0	8.00	11.0	32.1	3,415 @ 80
LT275/70R18	125R	OWL	7.0 - 8.5	8.00	11.0	33.2	3,640 @ 80
LT285/75R16	126R	OWL	7.5 - 9.0	8.00	11.3	32.8	3,750 @ 80
LT305/60R20	118S	BSL	8.5 - 11.0	9.00	12.2	34.4	2,910 @ 50
P215/65R17	98S	OWL	6.0 - 7.5	6.50	8.7	28.0	1,653 @ 44
P215/75R15	100S	OWL	5.5 - 7.0	6.00	8.5	27.7	1,742 @ 44

P225/70R15	100S	OWL	6.0 - 7.5	6.50	9.0	27.4	1,753 @ 44
P225/75R15	102S	OWL	6.0 - 7.5	6.00	8.8	28.3	1,874 @ 44
P225/75R16	104S	OWL	6.0 - 7.5	6.00	8.8	29.3	1,984 @ 44
P235/65R17	103S	OWL	6.5 - 8.5	7.00	9.5	29.1	1,929 @ 44
P235/70R15	102S	OWL	6.0 - 8.0	7.00	9.5	28.0	1,896 @ 44
P235/70R16	104S	OWL	6.0 - 8.0	7.00	9.5	29.0	1,984 @ 35
P235/70R17	108S	OWL	6.0 - 8.0	7.00	9.5	30.0	2,205 @ 50
P235/75R15	105S	OWL	6.0 - 8.0	6.50	9.3	28.9	2,028 @ 44
P235/75R16	109S	OWL	6.0 - 8.0	6.50	9.3	29.8	2,271 @ 50
P235/75R17	108S	OWL	6.0 - 8.0	6.50	9.3	30.9	2,205 @ 51
P245/65R17	105S	OWL	7.0 - 8.5	7.00	9.8	29.5	2,039 @ 44
P245/70R16	106S	OWL	6.5 - 8.0	7.00	9.8	29.5	2,094 @ 44
P245/70R16	106S	VSB	6.5 - 8.0	7.00	9.8	29.5	2,094 @ 44
P245/70R17	108S	VSB	6.5 - 8.0	7.00	9.8	30.6	2,205 @ 44
P245/75R16	109S	VSB	6.5 - 8.0	7.00	9.8	30.5	2,271 @ 44
P245/75R16	109S	OWL	6.5 - 8.0	7.00	9.8	30.5	2,271 @ 44
P255/65R16	106S	OWL	7.0 - 9.0	7.50	10.2	29.1	2,094 @ 44
P255/65R17	108S	OWL	7.0 - 9.0	7.50	10.2	30.1	2,205 @ 44
P255/70R16	109S	OWL	6.5 - 8.5	7.50	10.2	30.1	2,271 @ 44
P255/70R17	110S	OWL	6.5 - 8.5	7.50	10.2	31.1	2,337 @ 51
P255/70R18	112T	OWL	6.0 - 8.0	8.00	10.2	32.1	2,469 @ 51
P255/75R17	113S	OWL	6.5 - 8.5	7.00	10.0	32.1	2,535 @ 44
P265/50R20	106S	VSB	7.5 - 9.5	8.50	10.9	30.5	2,094 @ 44
P265/60R18	109T	VSB	7.5 - 9.5	8.00	10.7	30.5	2,271 @ 44
P265/65R17	110S	VSB	7.5 - 9.5	8.00	10.7	30.6	2,337 @ 44
P265/65R17	110S	OWL	7.5 - 9.5	8.00	10.7	30.6	2,337 @ 44
P265/65R18	112S	OWL	7.5 - 9.5	8.00	10.7	31.5	2,469 @ 51
P265/70R15	110S	OWL	7.0 - 9.0	8.00	10.7	29.7	2,337 @ 44
P265/70R16	111S	OWL	7.0 - 9.0	8.00	10.7	30.6	2,403 @ 44
P265/70R17	113R	VSB	7.0 - 9.0	8.00	10.7	31.7	2,535 @ 35
P265/70R17	113R	OWL	7.0 - 9.0	8.00	10.7	31.7	2,535 @ 35
P265/70R18	114S	OWL	7.0 - 9.0	8.00	10.7	32.6	2,601 @ 35
P265/75R15	112S	OWL	7.0 - 9.0	7.50	10.5	30.7	2,469 @ 44
P265/75R16	114S	OWL	7.0 - 9.0	7.50	10.5	31.7	2,601 @ 44
P275/55R20	111H	VSB	7.5 - 9.5	8.50	11.2	31.9	2,403 @ 51
P275/60R20	114S	OWL	7.5 - 9.5	8.00	11.0	33.0	2,601 @ 44
P275/60R20	114S	VSB	7.5 - 9.5	8.00	11.0	33.0	2,601 @ 44
P275/65R18	114T	OWL	7.5 - 9.5	8.00	11.0	32.1	2,601 @ 51