



OPTIMO H724



H724

- S & T-Rated
- U.T.Q.G. 500/A/B
- 60/65/70/75 Series
- White Sidewall
- Diagonal Serrated Band

The "Total Balance" Product has arrived. Leading a new Wave of innovation, Optimo H724 is designed to provide you with a longer mileage tire that delivers a comfortable ride, great handling, and all-season traction at a surprisingly affordable price. The tread pattern features a center rib designed for improved handling and stability when changing direction, and computer optimized grooves that maximize water evacuation for enhanced traction in wet and winter weather conditions.

Dimension Data

Pattern Code **H724** **PCR**

S-Code	Size	L / I & SS	Measuring Rim	Rim Width Range	Max. Load		Overall Diameter	Section Width	Tread Width	Tread Depth	Revs/ Mile	Sidewall Type
					Air	Load						
1010983	P175/70R13T	82T	5.0	4.5-5.5	44	1,036	22.7	7.0	4.6	9.5	916	DSB
1011704	P185/60R14T	82T	5.5	5.0-6.5	44	1,047	22.8	7.4	5.2	9.5	913	DSB
1011706	P195/60R14T	85T	6.0	5.5-7.0	44	1,135	23.2	7.9	5.4	10.0	894	DSB
1010987	P175/65R14T	81T	5.0	5.0-6.0	44	1,019	23.0	7.0	4.9	9.5	903	DSB
1010986	P185/65R14T	85T	5.5	5.0-6.5	44	1,124	23.5	7.4	5.2	9.5	885	DSB
1011694	P175/70R14T	84T	5.0	4.5-6.0	44	1,102	23.7	7.0	4.6	9.5	876	DSB
1010985	P185/70R14T	87T	5.5	4.5-6.0	44	1,201	24.3	7.4	4.8	10.0	857	DSB
1010999	P195/70R14T	90T	6.0	5.0-6.5	44	1,312	24.8	7.9	5.1	10.0	838	DSB
1011773	P205/70R14T	93T	6.0	5.0-7.0	44	1,433	25.4	8.2	5.3	10.0	819	WSW
1011004	P215/70R14T	96T	6.5	5.5-7.0	44	1,554	25.9	8.7	5.6	10.0	802	WSW
1011005	P185/75R14S	89S	5.0	4.5-6.0	44	1,290	25.0	7.2	4.6	10.0	832	WSW
1011010	P195/75R14S	92S	5.5	5.0-6.5	44	1,400	25.5	7.7	4.8	10.0	814	WSW
1010991	P205/75R14S	95S	5.5	5.0-7.0	44	1,532	26.1	8.0	5.0	10.0	795	WSW
1011002	P215/75R14S	98S	6.0	5.5-7.0	44	1,664	26.7	8.5	5.3	10.0	778	WSW
1011696	P185/60R15T	84T	5.5	5.0-6.5	44	1,102	23.7	7.4	5.2	9.5	875	DSB
1010993	P195/60R15T	87T	6.0	5.5-7.0	44	1,190	24.2	7.9	5.4	10.0	858	DSB
1011709	P205/60R15T	90T	6.0	5.5-7.5	44	1,301	24.7	8.2	5.7	10.0	842	DSB
1011697	P215/60R15T	93T	6.5	6.0-7.5	44	1,411	25.2	8.7	6.0	10.0	826	DSB
1011707	P185/65R15T	86T	5.5	5.0-6.5	44	1,168	24.4	7.4	5.2	9.5	850	DSB
1010997	P195/65R15T	89T	6.0	5.5-7.0	44	1,279	25.0	7.9	5.4	10.0	831	DSB
1011006	P205/65R15T	92T	6.0	5.5-7.5	44	1,400	25.5	8.2	5.7	10.0	816	DSB
1011710	P215/65R15T	95T	6.5	6.0-7.5	44	1,510	26.0	8.7	6.0	10.0	798	DSB
1011001	P205/70R15T	95T	6.0	5.0-7.0	44	1,499	26.3	8.2	5.3	10.0	789	WSW
1010989	P215/70R15T	97T	6.5	5.5-7.0	44	1,620	26.9	8.7	5.6	10.0	773	WSW
1011008	P225/70R15T	100T	6.5	6.0-7.5	44	1,753	27.4	9.0	5.9	10.5	757	WSW
1010990	P205/75R15S	97S	5.5	5.0-7.0	44	1,598	27.1	8.0	5.0	10.0	766	WSW
1010992	P215/75R15S	100S	6.0	5.5-7.0	44	1,742	27.7	8.5	5.3	10.0	751	WSW
1011009	P225/75R15S	102S	6.0	6.0-7.5	44	1,874	28.3	8.8	5.6	10.5	734	WSW
1010988	P235/75R15S XL	108S	6.5	6.0-8.0	50	2,183	28.9	9.3	5.8	10.5	720	WSW
1011000	P205/60R16T	91T	6.0	5.5-7.5	44	1,356	25.7	8.2	5.7	10.0	809	DSB
1011003	P215/60R16T	94T	6.5	6.0-7.5	44	1,477	26.1	8.7	6.0	10.0	795	DSB
1011011	P225/60R16T	97T	6.5	6.0-8.0	44	1,609	26.6	9.0	6.3	10.5	781	DSB
1011699	P235/60R16T	99T	7.0	6.5-8.5	44	1,709	27.1	9.4	6.6	10.5	767	DSB
1011698	P205/65R16T	94T	6.0	5.5-7.5	44	1,477	26.5	8.2	5.7	10.0	785	DSB
1011007	P215/65R16T	96T	6.5	6.0-7.5	44	1,565	27.0	8.7	6.0	10.0	769	DSB
1011700	P235/65R16T	101T	7.0	6.5-8.5	44	1,819	28.0	9.4	6.6	10.5	741	DSB
1011701	P215/60R17T	95T	6.5	6.0-7.5	44	1,521	27.2	8.7	6.0	10.0	765	DSB
1011703	P225/60R17T	98T	6.5	6.0-8.0	44	1,653	27.6	9.0	6.3	10.5	752	DSB
1011702	P215/65R17T	98T	6.5	6.0-7.5	44	1,653	28.0	8.7	6.0	10.0	741	DSB

DSB : Diagonal Serrated Band
 WSW : White Sidewall.
 Technical data subject to change without prior notice.