

[FIND HERCULES TIRES](#)

VEHICLE INFO

Select Year

Select Make

Select Model

SEARCH

Or

TIRE SIZE

Select Section Width

Select Aspect Ratio

Select Rim Diameter

SEARCH

Or

CATEGORY/SEGMENT

Category

SEARCH

[FIND HERCULES DEALERS](#)

LOCATION

Enter your city and state -or- zip code



[Overview/Warranty](#)

[Sizes and Specifications](#)

[IRONMAN RB-12](#)

An Ironman For All Seasons

The Ironman RB-12 delivers 365 days a year. And with 21 sizes, this all-season touring tire accommodates a wide scope of popular vehicles. And that's just for starters.



Features and Benefits

- Rim diameters from 13 to 16 inches, covering traditional 55/60/65/70 series offering
- Carries T, H, and V rated sizes
- Symmetric, five-rib tread design creates larger footprint for stability and performance
- Slotted shoulders, moderate siping and wide grooves enhance water evacuation and prevent hydroplaning
- Variable tread design reduces road noise and delivers ride comfort

Warranty

Ironman Tires have a 36-month limited warranty against manufacturer workmanship and defects from the date of purchase.

Please see your Ironman Tires or Hercules Tires dealer for more details.

FIND HERCULES TIRES

Tire Gallery / Touring / Ironman RB-12

VEHICLE INFO

Select Year

Select Make

Select Model

SEARCH

Or

TIRE SIZE

Select Section Width

Select Aspect Ratio

Select Rim Diameter

SEARCH

Or

CATEGORY/SEGMENT

Category

SEARCH



FIND HERCULES DEALERS

LOCATION

Enter your city and state -or- zip code

[Overview/Warranty](#) [Sizes and Specifications](#)

Item #	Tire Size & Service Description	Rim Width (in)	Max PSI	Max Load (lbs)	Max Load Dual (lbs)	Overall Diam. (in)	Section Width (in)	Tread Depth (32nds)	Ship Weight (lbs.)	Load Range/ PR	UTQG
91841	175/70R13 82T	5.0	44	1047	-	22.60	6.97	9.5	14.7	STD	440AB
91842	175/70R14 84T	5.0	44	1102	-	23.70	7.01	10.0	15.5	STD	440AB
91840	175/65R14 82T	5.0	44	1047	-	23.03	6.97	10.0	14.8	STD	440AB
91162	185/60R14 82H	5.5	44	1047	-	23.50	7.40	10.0	16.4	STD	440AB
91165	185/70R14 88T	5.5	44	1235	-	24.21	7.48	10.0	17.3	STD	440AB
91163	185/65R14 86T	5.5	44	1168	-	23.50	7.40	10.0	17.1	STD	440AB
91169	195/70R14 91T	6.0	44	1356	-	24.76	7.91	10.0	18.8	STD	440AB
91164	185/65R15 88T	5.5	44	1235	-	24.44	7.44	10.0	18.1	STD	440AB
91166	195/55R15 85V	6.0	44	1135	-	23.46	7.84	10.0	17.4	STD	440AB
91167	195/60R15 88T	6.0	44	1235	-	24.33	7.72	10.0	17.8	STD	440AB
91168	195/65R15 91T	6.0	44	1356	-	25.08	7.87	10.0	18.4	STD	440AB
91171	205/70R15 96T	6.0	44	1565	-	26.34	8.23	10.5	22.4	STD	440AB
91170	205/65R15 94T	6.0	44	1477	-	25.47	8.15	10.0	21.2	STD	440AB
91174	215/70R15 98T	6.5	44	1653	-	26.81	8.74	11.0	24.8	STD	440AB
91176	225/70R15 100T	6.0	44	1764	-	27.44	9.17	11.0	26.1	STD	440AB
92513	205/65R16 95H	6.0	44	1521	-	26.33	8.50	10.0	21.0	STD	440AB
91064	205/55R16 91T	6.5	44	1356	-	25.03	8.27	10.0	19.8	STD	440AB
91173	215/65R16 98T	6.5	44	1653	-	27.04	8.70	10.0	24.0	STD	440AB
91172	215/60R16 95T	6.5	44	1301	-	26.10	8.66	10.0	23.3	STD	440AB
91175	225/60R16 98T	6.5	44	1653	-	26.57	8.90	11.0	24.4	STD	440AB
92479	215/65R17 99T	6.5	44	1708	-	27.87	9.06	10.0	25.0	STD	440AB
92514	225/60R17 99H	6.5	44	1708	-	27.52	9.29	11.0	26.5	STD	440AB

92480	235/60R17 102H	7.0	44	1874	-	28.03	9.80	11.0	27.8	STD	440AB
-------	----------------	-----	----	------	---	-------	------	------	------	-----	-------

[Privacy Policy](#) | [Terms of Use](#) | © 2016 The Hercules Tire and Rubber Company