

# ECSTA STX

TREAD CODE: KL12



The Ecsta STX is part of Kumho Tire's Ecsta performance family and is focused on delivering premium high performance driving pleasure for your pickup truck, SUV and crossover utility vehicle. The directional tread and sidewall design delivers an eye-appealing combination for that sporty appearance. The Ecsta STX offers a perfectly balanced all-season performance compound and tread design to deliver year-round confident driving pleasure even in light snow. The Ecsta STX is available in a size range that covers both original equipment and plus fitment applications and offers a speed rating of either V or W to cater for the sportier applications.

## PERFORMANCE

- DRY 9
- WET 7
- NOISE 7
- WEAR 7
- COMFORT 6
- SNOW 3
- **OFF-ROAD** 4

Numeric ratings reflect how a tire compares against other Kumho tires of similar type. A rating of 10 indicates that the tire is designed to perform extremely well under those conditions. A rating of 4 or N/A (not applicable) indicates that the tire is not designed to excel in that area. 10 = Extremely Well, 5 = Acceptable, 1= Poor.

## SPECIAL FEATURES

- All-season performance.
- Two wide circumferential and lateral grooves evacuate water from under the tread area to minimize the risk of hydroplaning.

- Large, stable tread blocks promote a solid footprint and responsive steering under the most demanding conditions.
- Variable pitch tread blocks assist with road harmonics to produce a quiet ride, reducing vehicle cabin noise.
- Jointless construction and bead reinforcement ensures durability, large contact patch and steering response.
- Rim protector in lower sidewall safeguards wheels against curb damage.

## SAMPLE VEHICLES

BMW X5, Cadillac Escalade, Chevrolet 1500 Pickup, Chevrolet Tahoe, Chrysler Pacifica, Dodge Ram, Ford F150, GMC Envoy, GMC Yukon, Mercedes ML-430, Toyota Tacoma, Volkswagen Touareg

[Print Page](#)

### ECSTA STX

#### Ultra High Performance Light Truck & SUV

Tire Size	Product Code	Service Desc.	Construction	Sidewall	UTQG	Rim Width Range (inch)	Section Width on Measured Rim Width (inch)	Overall Dia (inch)	Tire Weight (lbs.)	Static Load Radius (inch)	RPM	Tread Depth (1/32")	Max Load Single (lbs)	Max Load Dual (lbs)	Max Inflation (psi)
255/65R16	1637613	109V		BSW	420 A/A	7.0 - 9.0	10.2 on 7.5	29.1	32.8	13.1	717	11.0	2271	0	51
255/55R18	1638313	109V	RF	BSW	420 A/A	7.0 - 9.0	10.4 on 8.0	29.0	34.6	13.3	716	11.0	2271		50
275/55R18	2101383	114V	RF	BSW	420 A/A	7.5 - 9.5	11.18 on 8.5	29.8	38.2	18.2	697	11.0	2601		51
235/60R18	2101323	107V	RF	BSW	420 A/A	6.5 - 8.5	9.5 on 7.0	29.1	31.4	17.7	714	11.0	2149		51
265/60R18	1638413	110V		BSW	420 A/A	7.5 - 9.5	10.7 on 8.0	30.5	37.7	13.9	683	11.0	2337		51
285/60R18	1635713	116V		BSW	420 A/A	8.0 - 10.0	11.5 on 8.5	31.5	42.9	14.2	662	11.0	2756		51
285/45R19	1861513	107W		BSW	420 A/A	9.0 - 10.5	11.2 on 9.5	29.1	35.7	13.4	714	11.0	2149		51

275/40R20	2103413	106W	RF	BSW	420 A/A	9.0 - 11.0	10.9 on 9.5	28.7	34.2	13.2	724	11.5	2094		51
275/45R20	1851913	106W		BSW	420 A/A	8.5 - 10.5	10.7 on 9.0	29.8	36.1	14.4	683	11.5	2094		51
265/50R20	2101283	111V	RF	BSW	420 A/A	7.5 - 9.5	10.9 on 8.5	30.5	38.1	18.2	681	11.5	2403		51
285/50R20	1832913	112V		BSW	420 A/A	8.0 - 10.0	11.7 on 9.0	31.3	41.7	14.5	666	11.0	2469		51
305/50R20	1648913	120V	RF	BSW	420 A/A	8.5 - 11.0	12.4 on 9.5	32.0	41.6	14.6	651	11.0	3086		50
275/55R20	1832813	117V	RF	BSW	420 A/A	7.5 - 9.5	11.2 on 8.5	31.9	41.7	14.8	652	11.0	2833		51
285/25R22	2101343	95V	RF	BWS	420 A/A	10.5	11.6 on 10.5	27.6	33.5	15.4	753	10.0	1521		51
285/30R22	1713413	101W	RF	BSW	420 A/A	9.5 - 10.5	11.4 on 10.0	28.8	35.2	13.6	724	11.5	1819		50
265/35R22	1851713	102W	RF	BSW	420 A/A	9.0 - 10.5	10.7 on 9.5	29.3	33.6	13.8	621	11.5	1874		51
265/40R22	2101303	106V	RF		420 A/A	9.0 - 10.5	10.7 on 9.5	30.5	37.2	14.1	681	11.0	2094	0	51
305/40R22	1682113	114V	RF	BSW	420 A/A	10.0 - 12.0	12.3 on 11.0	31.6	43.2	14.4	657	11.5	2601		50
275/45R22	2101403	112V	RF	BWS	420 A/A	8.5 - 10.0	10.8 on 9.0	31.7	41.6	18.6	655	11.0	2469		51
285/45R22	2101423	114V	RF	BWS	420 A/A	9.0 - 10.5	11.2 on 9.5	32.1	43.4	18.9	647	11.0	2601		51
305/45R22	1649113	118V	RF	BSW	420 A/A	9.5 - 11.5	11.9 on 10.0	32.8	44.9	15.2	636	11.0	2910		50
285/35R23	2101363	107V	RF	BSW	420 A/A	9.5 - 11.0	11.3 on 10.0	30.9	40.3	19.1	672	11.0	2149		50
305/40R23	1636513	115V	RF	BSW	420 A/A	10.0 - 12.0	12.3 on 11.0	32.6	43.4	15.3	636	11.0	2679		50

295/35R24	2101443	110V	RF	BSW	420 A/A	10.0 - 11.5	11.9 on 10.5	32.1	43.5	18.3	647	11.0	2337		51
305/35R24	1673913	114V	RF	BSW	420 A/A	10.0 - 12.0	12.3 on 11.0	32.4	43.6	15.3	640	11.0	2601		50
305/30R26	1681913	110V	RF	BSW	420 A/A	10.5 - 11.5	12.3 on 11.0	33.2	49.3	16.1	626	11.0	2337		50
325/35R28	1757613	120V	RF	BSW	420 A/A	10.0 - 12.0	13.3 on 11.0	37.0	62.1	17.4	563	11.5	3086		50
285/40R24	2101463	112V	RF	BSW	420 A/A	9.5 - 11.0	11.3 on 10.0	32.9	44.6	18.9	631	11.0	2469		51