

**KUMHO TIRE** 









## ROAD VENTURE AT51

Tread CODE : AT51

TREAD CLASSIFICATION : Symmetric

The legendary Road Venture AT51 offers world-class traction on soft terrain, and surprising comfort on the road. It's well-adapted to deep snow, muddy job sites and wet highways, with a ride that rivals many touring tires. Superbly balanced on/off-road performance, with exceptional efficiency.

### PERFORMANCE RATINGS

 <b>6</b> DRY	 <b>7</b> WET	 <b>6</b> NOISE	 <b>7</b> WEAR	 <b>6</b> COMFORT	 <b>10</b> SNOW	 <b>8</b> OFF ROAD
--	--	--	---	--	--	---

Numeric ratings reflect how a tire compares against other Kumho tires of similar type. A rating of 10 indicates that the tire is designed to perform extremely well under those conditions. A rating less than 4 or N/A (not applicable) indicates that the tire is not designed to excel in that area. 10 = Extremely Well, 5 = Acceptable, 1 = Poor.

### SIZE & TECHNICAL DATA

#### All-Terrain

Product Code	Tire Size	Service Desc.	Construction	Sidewall	UTQG	Rim Width Range (in.)	Section Width on Measured Rim Width	Overall Diameter	Tire Weight	Static Loaded Radius	Tread Depth (1/32")	Max Load Single	Max Load Double	Max Inflation (psi)	Country Origin	UPC
<b>15 Inch (1 sizes)</b>																
N/A	235/75R15	109T	XL	BSW	540 A/A	6.0 - 8.0	9.3 on 6.5	28.9	35	12.9	13.5	2183	0	50	USA	9.3 on 6.5
N/A	LT215/75R15	106/103R	D-Ply / 8-Ply	BSW	-	5.5 - 7.0	8.5 on 6.0	27.7	34.8	12.4	16	2095	1930	65	USA	8.5 on 6.0
N/A	LT235/75R15	104/101R	C-Ply / 6-Ply	BSW	-	6.0 - 7.0	9.3 on 6.5	28.9	35	12.9	16	1985	1820	50	USA	9.3 on 6.5
N/A	30X9.50R15	104R	C-Ply / 6-Ply	BSW	-	7.0 - 9.0	10.5 on 7.5	29.5	37.4	12.3	16	1985	0	50	USA	10.5 on 7.5
N/A	31X10.50R15	109R	C-Ply / 6-Ply	BSW	-	6.0 - 8.0	9.4 on 7.0	30.5	42	13	16	2270	0	50	USA	9.4 on 7.0
N/A	32X11.50R15	113R	C-Ply / 6-Ply	BSW	-	6.5 - 8.5	10.2 on 7.5	31.5	44.4	11.7	16	2535	0	50	USA	10.2 on 7.5
N/A	33X12.50R15	108R	C-Ply / 6-Ply	BSW	-	8.5 - 11.0	12.5 on 10.0	32.5	50.7	12.6	16	2205	0	35	USA	12.5 on 10.0

## 16 Inch (7 sizes)

N/A	LT215/85R16	115/112R	E-Ply / 10-Ply	BSW	-	5.5 - 7.0	8.5 on 6.0	30.4	44.1	13.6	16	2680	2470	80	USA	8.5 on 6.0
N/A	LT235/85R16	120/116R	E-Ply / 10-Ply	BSW	-	6.5 - 8.0	9.8 on 7.0	31.7	47.1	11.9	16	3042	2778	80	USA	9.8 on 7.0
N/A	P245/75R16	109T	-	BSW	540 A/A	6.5 - 8.5	10.2 on 7.5	30.5	36.2	12.1	13.5	2271	0	51	USA	10.2 on 7.5
N/A	245/70R16	111T	XL	BSW	540 A/A	6.5 - 8.0	9.8 on 7.0	29.5	36.3	13.3	13.5	2535	0	51	USA	9.8 on 7.0
N/A	P265/75R16	114T	-	BSW	540 A/A	7.0 - 9.0	10.5 on 7.5	31.7	41.9	12.3	13.5	2601	0	51	USA	10.5 on 7.5
N/A	LT225/75R16	115/112R	E-Ply / 10-Ply	BSW	-	7.0 - 8.5	9.8 on 7.0	29.3	42.2	11.5	16	2680	2470	80	USA	9.8 on 7.0
N/A	LT245/75R16	120/116R	E-Ply / 10-Ply	BSW	-	6.5 - 8.0	9.8 on 7.0	29.3	47.1	11.9	16	3042	2778	80	USA	9.8 on 7.0
N/A	LT265/75R16	123/120R	E-Ply / 10-Ply	BSW	-	7.0 - 8.0	10.5 on 7.5	31.7	52.6	13.5	16	3415	3085	80	USA	10.5 on 7.5
N/A	LT285/75R16	126/123R	E-Ply / 10-Ply	BSW	-	7.0 - 9.0	11.3 on 8.0	32.9	55.6	14.7	16	3750	3415	80	USA	11.3 on 8.0
N/A	LT315/75R16	121/118R	D-Ply / 8-Ply	BSW	-	8.0 - 11.0	12.3 on 8.5	34.6	65.4	15.2	16	3195	2910	50	USA	12.3 on 8.5
N/A	P235/70R16	104T	-	BSW	540 A/A	6.0 - 8.0	9.4 on 7.0	29	32.4	13.1	13.5	1984	0	51	USA	9.4 on 7.0
N/A	P255/70R16	109T	-	BSW	540 A/A	7.0 - 9.0	10.2 on 7.5	30.1	36.9	13.5	13.5	2271	0	51	USA	10.2 on 7.5
N/A	265/70R16	112T	-	BSW	540 A/A	7.0 - 9.0	10.7 on 8.0	30.6	41.1	13.7	13.5	2469	0	51	USA	10.7 on 8.0
N/A	LT305/70R16	124/121R	E-Ply / 10-Ply	BSW	-	8.0 - 9.5	12.2 on 9.0	32.8	61.2	12.4	16	3525	3195	65	USA	12.2 on 9.0

## 17 Inch (14 sizes)

N/A	LT235/80R17	120/117R	E-Ply / 10-Ply	BSW	-	6.0 - 7.5	9.3 on 6.5	31.8	47.6	11.2	16	3085	2835	80	USA	9.3 on 6.5
N/A	LT245/75R17	121/118R	E-Ply / 10-Ply	BSW	-	6.5 - 8.5	9.4 on 7.5	31.5	47.4	11.5	16	3195	2910	80	USA	9.4 on 7.5
N/A	LT255/75R17	111/108R	C-Ply / 6-Ply	BSW	-	7.0 - 9.0	10.6 on 8.5	32	43.5	11.9	15.5	2405	2205	50	USA	10.6 on 8.5
N/A	235/75R17	109T	-	BSW	540 A/A	6.0 - 8.0	9.3 on 6.5	30.9	36.1	12.3	13	2271	0	51	USA	9.3 on 6.5
N/A	P245/70R17	108T	-	BSW	540 A/A	6.5 - 8.0	9.8 on 7.0	30.6	36.3	13.8	13.5	2205	0	51	USA	9.8 on 7.0
N/A	P255/70R17	110T	-	BSW	540 A/A	5.5 - 7.0	8.5 on 6.0	31.1	39	13.6	13.5	2337	0	51	USA	8.5 on 6.0
N/A	P265/70R17	113T	-	BSW	540 A/A	6.0 - 7.5	9.3 on 6.5	31.7	38.5	12.4	13.5	2535	0	51	USA	9.3 on 6.5
N/A	LT245/70R17	119/116R	E-Ply / 10-Ply	BSW	-	6.5 - 8.0	9.8 on 7.0	30.6	46.6	13.8	16	3000	2755	80	USA	9.8 on 7.0
N/A	LT265/70R17	121/118R	E-Ply / 10-Ply	BSW	-	6.5 - 8.0	9.8 on 7.0	31.7	53	11.9	16	3195	2910	80	USA	9.8 on 7.0
N/A	LT275/70R17	114/110R	C-Ply / 6-Ply	BSW	-	7.0 - 8.0	10.5 on 7.5	32.2	46.2	12.3	16	2600	2335	50	USA	10.5 on 7.5
N/A	LT285/70R17	121/118R	E-Ply / 10-Ply	BSW	-	7.5 - 9.0	11.5 on 8.5	32.8	56.9	12.8	16	3195	2910	80	USA	11.5 on 8.5
N/A	LT315/70R17	121/118R	D-Ply / 8-Ply	BSW	-	8.0 - 11.0	12.2 on 9.5	34.4	62.9	13.5	16	3195	2910	50	USA	12.2 on 9.5
N/A	235/65R17	108T	XL	BSW	540 A/A	6.5 - 8.5	9.4 on 7.0	29.1	34.4	13.2	13.5	2205	0	65	USA	9.4 on 7.0

N/A	P245/65R17	105T	-	BSW	540 A/A	7.0 - 8.5	9.8 on 7.0	29.5	34.5	13.4	13.5	2039	0	51	USA	9.8 on 7.0
N/A	265/65R17	112T	-	BSW	540 A/A	7.5 - 9.5	10.7 on 8.0	30.6	39.1	13.8	13.5	2469	0	51	USA	10.7 on 8.0

18 Inch (15 sizes)

N/A	255/70R18	113T	-	BSW	540 A/A	6.5 - 8.5	10.2 on 7.5	32.1	41.1	14.5	13	2535	0	51	USA	10.2 on 7.5
N/A	P265/70R18	114T	-	BSW	540 A/A	6.5 - 8.0	9.8 on 7.0	32.6	41.6	11.9	13.5	2601	0	51	USA	9.8 on 7.0
N/A	LT265/70R18	124/121R	E-Ply / 10-Ply	BSW	-	7.0 - 8.5	10.7 on 8.0	32.6	56.7	12.3	15.5	3525	3195	80	USA	10.7 on 8.0
N/A	LT275/70R18	125/122R	E-Ply / 10-Ply	BSW	-	7.0 - 8.5	11.0 on 8.0	33.2	57.7	12.5	16	3640	3305	80	USA	11.0 on 8.0
N/A	265/65R18	114T	-	BSW	540 A/A	7.5 - 9.0	11.5 on 8.5	31.5	42.2	12.8	13	2601	0	51	USA	11.5 on 8.5
N/A	P275/65R18	114T	-	BSW	540 A/A	7.5 - 9.5	11.0 on 8.0	32.1	44.4	13.4	13.5	2601	0	51	USA	11.0 on 8.0
N/A	LT275/65R18	123/120R	E-Ply / 10-Ply	BSW	-	7.5 - 9.0	11.0 on 8.0	32.1	54.5	12.5	16	3415	3085	80	USA	11.0 on 8.0
N/A	LT285/65R18	125/122R	E-Ply / 10-Ply	BSW	-	7.0 - 8.5	11.0 on 8.0	32.6	57.3	14.9	16	3640	3305	80	USA	11.0 on 8.0
N/A	265/60R18	110T	-	BSW	540 A/A	7.5 - 9.5	10.7 on 8.0	30.5	39.9	13.9	13	2337	0	51	USA	10.7 on 8.0

20 Inch (9 sizes)

N/A	LT265/60R20	121/118R	E-Ply / 10-Ply	BSW	-	7.5 - 9.5	10.7 on 8.0	32.5	53.7	14.8	16	3195	2910	80	USA	10.7 on 8.0
N/A	LT275/65R20	126/123R	E-Ply / 10-Ply	BSW	-	7.5 - 9.0	11.0 on 8.0	34.1	57.2	12.5	16	3750	3415	80	USA	11.0 on 8.0
N/A	P275/60R20	114T	-	BSW	540 A/A	7.5 - 9.5	11.0 on 8.0	33	44.3	12.7	13.5	2601	0	51	USA	11.0 on 8.0
N/A	P275/55R20	111T	-	BSW	540 A/A	7.5 - 9.5	11.2 on 8.5	31.9	45.2	14.6	13.5	2403	0	51	USA	11.2 on 8.5
N/A	LT285/55R20	122/119R	E-Ply / 10-Ply	BSW	-	8.0 - 10.0	11.7 on 9.0	32.4	57.5	12.6	16	3305	3000	80	USA	11.7 on 9.0
N/A	LT305/55R20	121/118R	E-Ply / 10-Ply	BSW	-	8.5 - 11.0	12.4 on 9.5	33.2	64.1	15.1	15.5	3195	2910	65	USA	12.4 on 9.5
N/A	35X12.50R20	121R	E-Ply / 10-Ply	BSW	-	8.5 - 11.0	12.5 on 10.0	34.5	65.4	15.4	15.5	3195	0	65	USA	12.5 on 10.0



LOCATE NEARBY DEALERS

ATLANTIC TIRE & AUTO

1010 NORTH FAIRFAX AVENUE  
 WEST HOLLYWOOD, CA 90046  
**(323) 654-0814**

DISTANCE FROM 90010 < 1 Mile

ATLANTIC TIRE & AUTO

1010 NORTH FAIRFAX AVENUE  
 WEST HOLLYWOOD, CA 90046  
**(323) 654-0814**

DISTANCE FROM 90010 < 1 Mile

ATLANTIC TIRE & AUTO

1010 NORTH FAIRFAX AVENUE  
 WEST HOLLYWOOD, CA 90046  
**(323) 654-0814**

DISTANCE FROM 90010 < 1 Mile

SPECIAL FEATURES

- Class-leading performance in the mud and snow, with an angled chamfer that creates hundreds of gripping edges, and a deep, tapered tread block that promotes self-cleaning.
- Engineered for a quiet, comfortable ride, with a symmetric tread design and variable-pitch tread blocks to reduce road harmonics.
- Excellent grip and stability in heavy weather, with deep central grooves to channel rain and snow away quickly.
- For long tread wear and fuel efficiency, the dual silicone compound is engineered to cool quickly and wear evenly.

## SAMPLE VEHICLES

- Chevrolet Pickup; Dodge/Ram Pickup; Ford Pickup; Hummer H2, H3; Jeep Wrangler; Nissan Titan; Toyota Tundra

## WARRANTIES

### KUMHO MANUFACTURER'S WARRANTY

All Kumho brand passenger and light truck tires are covered for a maximum of 72 months from the date of purchase.

### 30-DAY

If you are not completely satisfied with your eligible Kumho brand replacement tire, the tire can be returned for a full refund or exchange within 30 days from the purchase date. Exclusions may apply. See more.