

# ROAD VENTURE MT

TREAD CODE: KL71



The Road Venture MT KL71 is a race proven, ground pounding mud slinging off-road tire with surprisingly good on-road manners. The Kumho MT is an excellent choice for off-road enthusiasts or individuals that require a high traction tire for their work environment. The extra deep cut-and-chip resistant directional compound will withstand the most brutal of environments while the tread design is engineered to promote self cleaning. The size offerings range from flotation sizes for the lifted vehicles to LT-metric sizes in load ranges C, D and E for the applications that require extra load-carrying capacity.

## PERFORMANCE

- DRY 6
- WET 6
- NOISE 5
- WEAR 5
- COMFORT 5
- SNOW 8
- **OFF-ROAD 10**

Numeric ratings reflect how a tire compares against other Kumho tires of similar type. A rating of 10 indicates that the tire is designed to perform extremely well under those conditions. A rating of 4 or N/A (not applicable) indicates that the tire is not designed to excel in that area. 10 = Extremely Well, 5 = Acceptable, 1= Poor.

## SPECIAL FEATURES

- Durable cut-and-chip resistant tread endures the most demanding environments.
- Dual compound tread prevents heat buildup, and blocks out impact and noise from the road surface.
- High tensile full-width steel belts and jointless cap plies enhance durability and reduce noise.
- Dual body plies reduce the stress of on-and-off-road use.

- Dual pitch, off-center staggered tread blocks reduce road harmonics and increase climbing ability and off-road traction.
- Shoulder tread area features stone ejectors to prevent stone drilling. The stone ejectors also promote self-cleaning in a mud environment.
- Phenomenal cosmetic appearance.

# SAMPLE VEHICLES

Chevrolet Silverado, Dodge Dakota, Dodge Ram Series, Ford F Series, Ford Ranger, Isuzu Rodeo, Jeep Wrangler, Toyota Tacoma

## ROAD VENTURE MT

### Mud Terrain Light Truck & SUV

Tire Size	Product Code	Service Desc.	Construction	Sidewall	UTQG	Rim Width Range (inch)	Section Width on Measured Rim Width (inch)	Overall Dia (inch)	Tire Weight (lbs.)	Static Load Radius (inch)	RP M	Tread Depth (1/32")	Max Load Single (lbs)	Max Load Dual (lbs)	Max Inflation (psi)
31X10.50R15	1764313	109Q	C	BSW	◆	7.0 - 9.0	10.6 on 8.5	30.6	45.4	13.6	680	18.5	2270		50
32X11.50R15	1871513	113Q	C	BSW	◆	8.0 - 10.0	11.4 on 9.0	31.8	50.9	14.0	658	20.0	2535		50
33X12.50R15	1803713	108Q	C	BSW	◆	8.5 - 11.0	12.5 on 10.0	32.3	53.7	14.2	638	18.5	2205		35
35 X 12.50R15	1861313	113Q	C	BSW	◆	8.5 - 11.0	13.6 on 10.0	34.7	67.9	17.0	599	21.0	2535		35
LT235/75R15	1854113	104/101Q	C	BSW	◆	6.0 - 7.0	9.3 on 6.5	29.1	40.9	11.3	719	18.0	1985	1820	50
LT305/70R16	1912013	121/124 Q	E	BSW	◆	8.0- 9.5	12.2 on 9.0	33.1	64.5	14.6	628	18.5	3195	3195	65
LT225/75R16	1854013	110/107Q	D	BSW	◆	6.0 - 7.0	8.8 on 6.0	29.5	42.6	13.3	708	18.0	2335	2150	65
LT245/75R16	1854213	120/116Q	E	BSW	◆	6.5 - 7.5	9.8 on 7.0	30.7	50.0	13.7	681	18.5	3042	2778	80
LT265/75R16	1854313	120/116 Q	D	BSW	◆	7.0 - 8.0	10.5 on 7.5	31.9	52.5	14.2	656	18.5	3000	2755	65

LT265/75R16	1911913	123/120Q	E	BSW	◆	7.0 - 8.0	10.5 on 7.5	31.9	55.9	12.4	656	18.5	3415	3085	80
LT285/75R16	1917713	126/123 Q	E	BSW	◆	7.5 - 9.0	11.3 on 8.0	32.8	58.8	14.5	633	18.5	3750	3415	80
LT315/75R16	2107223	127/124Q	E	BSW	◆	8.0 - 10.0	12.3 on 8.5	34.5	78.2	22.4	602	18.5	3860	3525	65
205/80R16	1853913	104Q	XL	BSW	◆	5.5 - 7.0	8.0 on 5.5	28.9	34.9	13.1	719	18.0	1985		50
LT235/85R16	1875313	120/116Q	E	BSW	◆	6.0 - 7.5	9.3 on 6.5	32.0	51.0	14.2	654	18.5	3042	2778	80
35X12.50R17	1912113	124Q	E	BSW	◆	8.5 - 11.0	12.5 on 10.0	34.8	75.7	13.4	608	17.0	3525	0	65
LT265/70R17	1871413	112/109Q	C	BSW	◆	7.0 - 8.5	10.7 on 8.0	31.9	54.2	14.3	651	18.5	2470	2270	50
LT265/70R17	1911813	121/118Q	E	BSW	◆	7.0 - 8.5	10.7 on 8.0	31.9	54.2	14.3	651	18.5	3195	2910	80
LT285/70R17	2119043	121/118Q	D	BSW	◆	7.5 - 9.0	11.5 on 8.5	32.7	.0	.0	635	18.5	3195	2910	65
LT315/70R17	1871313	121/118Q	D	BSW	◆	8.5 - 10.0	12.7 on 9.5	34.6	71.8	15.4	600	18.5	3195	2910	50
33X12.50R18	2108023	118Q	E	BSW	◆	8.5 - 11.0	12.7 on 10.0	33.0	74.0	20.7	630	21.0	2910		65
35X12.50R18	1825213	118Q	D	BSW	◆	8.5 - 11.0	11.4 on 10.0	34.8	74.1	16.2	597	21.5	2910		50
38X15.50R18	1831613	128Q	D	BSW	◆	11.0 - 13.0	14.3 on 12.0	37.8	94.6	17.5	550	21.5	3970		50
33X12.50R20	2107263	114Q	E	BSW	◆	8.5 - 11.0	12.5 on 10.0	32.8	67.3	15.0	0	21.0	2600		65
37X13.50R20	1829613	127Q	E	BSW	◆	8.5 - 11.0	12.5 on 11.0	36.8	84.1	17.1	565	21.5	3860		65
38X15.50R20	1830613	125Q	D	BSW	◆	11.0 - 13.0	14.3 on 12.0	37.8	93.9	17.5	550	21.5	3635		50

37X13.50R22	1825413	123Q	E	BSW	◆	8.5 - 11.0	12.5 on 11.0	36.8	79.4	17.1	565	21.5	3420		65
37X14.00R24	1767513	115Q	D	BSW	◆	9.0 - 12.5	13.6 on 11.0	36.2	78.9	16.8	574	18.5	2680		50
38X14.00R24	1831513	118Q	D	BSW	◆	9.0 - 11.5	14.1 on 11.0	37.8	83.1	17.5	550	21.5	2910		50