

SOLUS KR21

TREAD CODE: KR21



Kumho Tire offers the Solus KR21 with a phenomenal Quality Assurance Package featuring an 85,000 limited tread life warranty, 24-hour roadside assistance and a road hazard program covering the first 2/32" of tread wear. The Solus KR21 is available in a wide range of sizes that covers sedans, mid-sized vehicles, mini-vans and crossover utility vehicles. The symmetric all-season tread design of the KR21 delivers exceptional ride comfort, wet traction, dry traction and performs efficiently in light snow.

PERFORMANCE

- DRY 7
- WET 7
- NOISE 8
- WEAR 9
- COMFORT 9
- SNOW 8
- **OFF-ROAD** N/A

Numeric ratings reflect how a tire compares against other Kumho tires of similar type. A rating of 10 indicates that the tire is designed to perform extremely well under those conditions. A rating of 4 or N/A (not applicable) indicates that the tire is not designed to excel in that area. 10 = Extremely Well, 5 = Acceptable, 1= Poor.

SPECIAL FEATURES

- Advanced carbon tread compound delivers outstanding wet and dry grip.

- Nylon belt edge layers, normally found in high performance tires, provide a higher degree of durability and stability.
- Full-depth sipes, effective for the life of the tire, cut through water film for greater wet traction and maximize all-season performance, even during harsh winters.
- Jointless, spiral-wound bead bundles isolate road harshness, provide enhanced comfort, lower vibration and allow for a more precise tire to rim fit.
- Kumho's ESCOT Tension Control technology increases the tension in the bead and shoulder area, providing improved handling and steering response.

SAMPLE VEHICLES

Acura 3.2 TL, Acura Integra, Dodge Caravan, Ford Windstar, Honda Accord, Honda Civic, Lincoln Town Car, Mazda 6, Nissan Sentra, Toyota Camry, Toyota Corolla

[Print Page](#)

SOLUS KR21

Touring All Season

Tire Size	Product Code	Service Desc.	Sidewall	UTQG	Rim Width Range (inch)	Section Width on Measured Rim Width (inch)	Overall Dia (inch)	Tire Weight (lbs.)	Static Load Radius (inch)	RPM	Tread Depth (1/32")	Max Load Single (lbs)	Max Inflation (psi)
P175/70R13	1899813	82T	BSW	640 A/B	4.5 - 6.0	7.0 on 5.0	22.7	14.6	8.8	916	10.5	1034	44
P185/70R13	1906313	85T	BSW	640 A/B	4.5 - 6.0	7.4 on 5.5	23.2	15.4	9.1	894	11.0	1133	44
P155/80R13	1905813	79T	WSW	640 A/B	4.0 - 5.0	6.2 on 4.5	22.8	13.5	8.8	922	10.0	957	44
P185/60R14	1899913	82T	BSW	640 A/B	5.0 - 6.5	7.4 on 5.5	22.8	15.3	8.9	913	11.0	1045	44
P195/60R14	1901013	85T	BSW	640 A/B	5.5 - 7.0	7.9 on 6.0	23.2	17.5	9.1	894	11.0	1133	44
P175/65R14	1906013	81T	BSW	640 A/B	5.0 - 6.0	7.0 on 5.0	23.0	15.4	9.0	904	10.5	1016	44
P185/65R14	1900013	85T	BSW	640 A/B	5.0 - 6.5	7.4 on 5.5	23.5	17.0	9.2	885	11.0	1122	44

P195/65R14	1906613	88T	BSW	640 A/B	5.5 - 7.0	7.9 on 6.0	24.0	17.9	9.4	865	11.0	1232	44
P185/70R14	1906413	87T	BSW	640 A/B	4.5 - 6.0	7.4 on 5.5	24.2	16.4	9.5	857	11.0	1199	44
P195/70R14	1906713	90T	BSW	640 A/B	5.0 - 6.5	7.9 on 6.0	24.8	17.8	9.7	838	11.0	1309	44
P205/70R14	1900713	95T	BSW	640 A/B	5.0 - 7.0	8.2 on 6.0	25.4	19.4	9.9	819	11.0	1521	44
P215/70R14	1900813	96T	BSW	640 A/B	5.5 - 7.0	8.7 on 6.5	25.9	21.2	10.1	802	11.0	1554	44
P185/75R14	1906513	89T	WSW	640 A/B	4.5 - 6.0	7.2 on 5.0	25.0	17.6	9.7	832	11.0	1287	44
P185/75R14	2104303	89T	BSW	640 A/B	4.5 - 6.0	7.2 on 5.0	25.0	17.4	9.7	832	11.0	1287	44
P195/75R14	1906813	92T	WSW	640 A/B	5.0 - 6.5	7.7 on 5.5	25.5	19.2	9.9	814	11.0	1518	44
P195/75R14	2104323	92T	BSW	640 A/B	5.0 - 6.5	7.7 on 5.5	25.5	18.7	9.9	814	11.0	1518	44
P205/75R14	1907313	95T	WSW	640 A/B	5.0 - 7.0	8.0 on 5.5	26.1	20.4	10.2	795	11.0	1529	44
P205/75R14	2104343	95T	BSW	640 A/B	5.0 - 7.0	8.0 on 5.5	26.1	20.5	10.2	795	11.0	1529	44
P195/60R15	1900213	87T	BSW	680 A/B	5.5 - 7.0	7.9 on 6.0	24.2	18.7	9.4	858	11.0	1188	44
P205/60R15	1900413	90T	BSW	680 A/B	5.5 - 7.5	8.2 on 6.0	24.7	19.9	9.6	842	11.0	1298	44
P215/60R15	1907513	93T	BSW	680 A/B	6.0 - 7.5	8.7 on 6.5	25.2	22.5	9.8	826	11.0	1408	44
P225/60R15	1908113	95T	BSW	680 A/B	6.0 - 8.0	9.0 on 6.5	25.6	23.3	10.0	811	11.0	1518	44

P185/65R15	1900113	86T	BSW	680 A/B	5.0 - 6.5	7.4 on 5.5	24.5	17.7	9.5	850	11.0	1168	44
P195/65R15	1900313	89T	BSW	680 A/B	5.5 - 7.0	7.9 on 6.0	25.0	19.2	9.8	830	11.0	1276	44
P205/65R15	1900613	92T	BSW	680 A/B	5.5 - 7.5	8.2 on 6.0	25.5	20.7	9.9	818	11.0	1397	44
P215/65R15	1907613	95T	BSW	680 A/B	6.0 - 7.5	8.7 on 6.5	26.0	23.4	10.1	798	11.0	1507	44
P205/70R15	1907213	95T	WSW	680 A/B	5.0 - 7.0	8.2 on 6.0	26.3	21.5	10.3	789	11.0	1496	44
P205/70R15	2104363	95T	BSW	680 A/B	5.0 - 7.0	8.2 on 6.0	26.3	20.4	10.3	789	11.0	1496	44
P215/70R15	1907813	97T	WSW	680 A/B	6.0 - 7.5	8.7 on 6.5	26.8	23.5	10.5	773	11.0	1617	44
P215/70R15	2104483	97T	BSW	680 A/B	6.0 - 7.5	8.7 on 6.5	26.8	23.3	10.5	773	11.0	1617	44
P225/70R15	1908313	100T	BSW	680 A/B	6.0 - 7.5	9.0 on 6.5	27.4	25.4	10.7	757	11.0	1749	44
P235/70R15	1908913	102T	BSW	680 A/B	6.0 - 8.0	9.4 on 7.0	28.0	26.9	10.9	742	11.0	1896	44
P205/75R15	1907413	97T	WSW	680 A/B	5.0 - 7.0	8.0 on 5.5	27.1	22.0	10.6	766	11.0	1595	44
P205/75R15	2104383	97T	BSW	680 A/B	5.0 - 7.0	8.0 on 5.5	27.1	21.6	10.6	766	11.0	1595	44
P215/75R15	1908013	100T	WSW	680 A/B	5.5 - 7.0	8.7 on 6.5	27.7	24.2	10.8	751	11.0	1738	44
P215/75R15	2104403	100T	BSW	680 A/B	5.5 - 7.0	8.7 on 6.5	27.7	23.8	10.8	751	11.0	1738	44
P225/75R15	1908513	102T	WSW	680 A/B	6.0 - 7.5	8.8 on 6.0	28.3	25.8	11.0	734	11.0	1870	44

P225/75R15	2104423	102T	BSW	680 A/B	6.0 - 7.5	8.8 on 6.0	28.3	25.7	11.0	734	11.0	1870	44
P235/75R15	1909113	105T	WSW	680 A/B	6.0 - 8.0	9.2 on 6.5	28.9	27.5	11.1	720	11.0	2028	44
P235/75R15	2104443	105T	BSW	680 A/B	6.0 - 8.0	9.2 on 6.5	28.9	27.6	11.1	720	11.0	2028	44
P235/75R15	1909213	108T	WSW	680 A/B	6.0 - 8.0	9.2 on 6.5	28.9	27.7	11.1	720	11.0	2183	44
P235/75R15	2104463	108T	BSW	680 A/B	6.0 - 8.0	9.2 on 6.5	28.9	29.9	11.1	720	11.0	2183	44
P205/55R16	1906913	89T	BSW	680 A/B	5.5 - 7.5	8.4 on 6.5	24.9	21.1	9.7	835	11.0	1276	44
P205/60R16	1900513	91T	BSW	680 A/B	5.5 - 7.5	8.2 on 6.0	25.7	21.3	10.0	812	11.0	1353	44
P215/60R16	1909313	94T	BSW	680 A/B	6.0 - 7.5	8.7 on 6.5	26.1	24.3	10.2	795	11.0	1474	44
P225/60R16	1900913	97T	BSW	680 A/B	6.0 - 8.0	9.0 on 6.5	26.6	25.3	10.4	781	11.0	1606	44
P235/60R16	1908613	99T	BSW	680 A/B	6.5 - 8.5	9.4 on 7.0	27.1	27.4	10.6	767	11.0	1705	44
P205/65R16	1907113	94T	BSW	680 A/B	5.5 - 7.5	8.2 on 6.0	26.5	21.6	10.3	785	11.0	1474	44
P215/65R16	1907713	96T	BSW	680 A/B	6.0 - 7.5	8.7 on 6.5	27.0	25.2	10.5	769	11.0	1518	44
P235/65R16	2100573	103T	BSW	680 A/B	6.5 - 8.5	9.5 on 7.0	29.0	28.8	13.0	716	11.0	1929	44
P215/70R16	1907913	99T	BSW	680 A/B	5.5 - 7.0	8.7 on 6.5	27.8	25.2	17.2	747	11.0	1705	44
P225/70R16	1908413	101T	BSW	680 A/B	6.0 - 7.5	9.0 on 6.5	28.7	26.8	17.9	724	11.0	1819	44

P235/70R16	1909013	104T	BSW	680 A/B	6.0 - 8.0	9.5 on 7.0	29.2	28.5	18.3	711	11.0	1984	44
P225/60R17	1908213	98T	BSW	680 A/B	6.0 - 8.0	9.0 on 6.5	27.6	27.3	12.6	753	11.0	1649	44
P235/60R17	2100473	100T	BSW	680 A/B	6.5 - 8.5	9.4 on 7.0	28.1	28.9	12.8	739	11.0	1764	44
P235/65R17	1908713	103T	BSW	680 A/B	6.5 - 8.5	9.5 on 7.0	29.0	30.1	13.2	716	11.0	1929	44
P235/65R18	1908813	104T	BSW	680 A/B	6.5 - 8.5	9.5 on 7.0	30.0	32.0	13.2	692	11.0	1984	44