

MICHELIN® 4x4 Diamaris®

Original Equipment, High-Performance Tire. Designed as original equipment on many premium European Crossovers and SUVs, MICHELIN® 4x4 Diamaris® tires allow drivers to take full advantage of the high-performance capabilities of these vehicles.



High-Speed Confidence.¹ BAZ Technology™ helps increase stability and responsiveness on the highway by maintaining the tire's shape at high speeds.

Wet Grip, Outstanding Dry Grip. Tread compounds derived from our ultra-high performance sports car tires provide wet grip while leading the competition in dry grip.²

Chosen by Some of the World's Best. The MICHELIN® 4x4 Diamaris® tire is chosen by some of the world's most demanding vehicle manufacturers for its performance on SUVs and Crossovers — including the Porsche Cayenne, Mercedes-Benz ML and BMW X5.

Original Equipment Fitments:

Most performance Crossovers and SUVs. Available in 19- and 20-inch sizes with V- and W-speed ratings.

¹ Exceeding the safe, legal speed limit is neither recommended nor endorsed.

² Based on third-party dry braking test results versus Pirelli Scorpion Zero™ tires, Continental 4x4 Sport Contact™ tires, Bridgestone® Turanza® ER30 tires and Dunlop® SP Sport 9000 tires.

Tire Size	Service Description	MSPN	Rim Width Range (inches)	Section Width on Measuring Rim Width (inches)	Overall Diameter	Tread Depth (in/32nds)	Rev/Mile @ 45 mph	Max. Load Single (lbs@psi)	O.E. Fitments
215/65R16	98H	20642	6.0 - 7.5	8.7 on 6.5	27.0	10.0	770	1503@51	VW
235/55R17	99H	27260	6.5 - 8.5	9.7 on 7.5	27.2	10.0	766	1554@51	VW
235/65R17	104W	27224	6.5 - 8.5	9.4 on 7.0	29.1	10.0	716	1984@51	AU
235/65R17/XL	108V N0	99915	6.5 - 8.5	9.4 on 7.0	29.1	10.0	715	2005@50†	P, VW
255/50R19	103V *	77861	7.0 - 9.0	10.8 on 9.0	29.1	10.0	714	1754@51†	BM
255/50R19	103W	34990	7.0 - 9.0	10.4 on 8.0	29.1	10.0	715	1754@51	
275/45R19/XL	108Y N0	93968	8.5 - 10.5	10.8 on 9.0	28.8	10.0	722	2005@50†	P
275/55R19	111V	16017	7.5 - 9.5	11.2 on 8.5	30.9	10.0	673	2185@51	
285/45R19	107V *	98256	9.0 - 10.5	11.4 on 10.0	29.1	10.0	714	1953@51†	BM
255/50R20/XL	109Y	20646	7.0 - 9.0	10.4 on 8.0	30.0	10.0	691	2065@50	LR
275/40R20	102W *	43164	9.0 - 11.0	11.0 on 9.5	28.7	10.0	724	1704@51†	BM
275/40R20/XL	106Y N1	37751	9.0 - 11.0	10.7 on 9.0	28.8	10.0	724	1903@50†	P, VW
275/40R20/XL	106Y	91196	9.0 - 11.0	10.9 on 9.5	28.6	8.5	726	1904@50	LR
275/50R20	109W	63067	7.5 - 9.5	11.2 on 8.5	30.9	10.0	674	2065@51	
285/35R22	102W	56214	9.5 - 11.0	11.4 on 10.0	29.9	10.0	695	1704@51†	
315/35R20	106W	31073	10.5 - 12.5	12.6 on 11.0	28.6	10.0	726	1903@51	

Original Equipment Key: AU = Audi, BM = BMW, LR = Land Rover, P = Porsche, VW = Volkswagen

Service Description Key: * = BMW, N0 or N1 = Porsche

XL = Extra Load

† Passenger sizes used in LT/SUV applications have reduced load capacity. This will differ from maximum load branded on the tire sidewall.

UTQG = 220/AA/A

Available Sidewall = BW

See pages 100 – 101 for important product information.