

Your Search: Name : LTX M/S

LTX® M/S

SUV/Crossover, Light Truck

All Season Tire

A long-time consumer favorite, MICHELIN® LTX® M/S tires offer long tread life and true all-season traction capabilities.



Benefits of Michelin

- Up to 15% Better Snow Traction Than the Competition¹
- Three-Steel-Belt Durability
- Wears Evenly, Long Lasting

Michelin Performance Rating:

- 8 WEAR LIFE
- 8 FUEL EFFICIENCY
- 7 OFF ROAD
- 7 BRAKING
- 8 COMFORT

Average User Ratings:

(1452 review s)

Tire Warranties:



Warranties (2 Warranties)



60,000 Mile Manufacturer's Treadwear Limited Warranty

LTX® M/S tires carry an additional 60,000 mile limited warranty for treadwear or mileage.



Standard Limited Warranty (All Michelin® Tires)

All Michelin® tires have a Standard Manufacturer's Limited Warranty, which covers defects in workmanship and materials for the life of the original usable tread, or for 6 years from date of purchase, whichever occurs first. See warranty for details

Available on:

LTX® M/S

Speed Rating: [H, R, S, T]

Tech Specs (11 part numbers)

Please use [Export to excel](#) link in order to download and print technical specification data.

¹ Compared against Bridgestone® Dueler™ H/T, Goodyear® Fortera® featuring TripleTred Technology™, and Goodyear® Wrangler® featuring SilentArmor Technology™.

² Using four LT265/75R16/E/TT tires inflated at 80 psi.

OE Code [Original Equipment Key]: DC = DaimlerChrysler, F = Ford, HO = Honda, I = Infiniti, L = Lexus, MA = Mazda, N = Nissan, T = Toyota

* Passenger sizes used in Light Truck/SUV applications have reduced load capacity. This will differ from the maximum load branded on the tire sidewall.

Government UTQG Ratings do not apply to light truck sized tires.

XL = Extra Load

>> The sizes shown are average design values for tires measured on specified measuring rim widths. Some tires may vary from this value by +/-3% of the section height (affecting overall diameter), and +/-4% of the section width.

>> Section width varies approximately 0.2" (5mm) for every 0.5" change in rim width.

>> Tread patterns are often tuned to accommodate different tire widths. Tires for a particular dimension of a given tireline may vary in appearance from the tire shown in the photograph.

WARNING: Serious or fatal injury may result from tire failure due to underinflation or overloading. To ensure correct air pressure and vehicle load, refer to vehicle owner's manual or tire information placard on the vehicle. Serious injury or death may result from explosion of tire/rim assembly due to improper mounting. Only tire professionals should mount tires and they should never inflate beyond 40 psi to seat the beads. Before mixing types of tires in any configuration on any vehicle, be sure to check the vehicle owner's manual for its recommendations.

DANGER: Never mount a 16" diameter tire on a 16.5" rim.

DANGER: Never mount a 17" diameter tire on a 17.5" rim.

Inflation pressure increase must not exceed the maximum pressure branded on the tire sidewall. When a customer requests a replacement tire with a lower speed rating than the original equipment tire, you must clearly communicate to him or her that the handling of the vehicle may be different, and that its maximum speed capability is limited to that of the lowest speed-rated tire on the vehicle. Exceeding the lawful speed limit is neither recommended nor endorsed.

For high-speed driving, additional inflation pressure and possibly reduced tire loading and/or upsizing is required. In the absence of specific recommendations by the vehicle manufacturer, use the following guidelines based on those in the European Tyre and Rim Technical Organization Standards Manual.

For speeds over 160km/h (100 mph), load and inflation must be adjusted according to the table below.

S-Speed Rated Sizes:

Maximum Speed (mph) 100 106 112

Inflation Increase (psi) 0.0 1.0 2.0

Load Capacity (% of max.) 100 100 100

T-Speed Rated Sizes:

Maximum Speed (mph) 100 106 112 118

Inflation Increase (psi) 0.0 1.0 2.0 3.0

Load Capacity (% of max.) 100 100 100 100

H-Speed Rated Sizes:

Maximum Speed (mph) 100 106 112 118 124 130

Inflation Increase (psi) 0.0 1.0 2.0 3.0 4.0 5.0

Load Capacity (% of max.) 100 100 100 100 100 100