

Your Search: Name : Pilot Sport PS2

Pilot® Sport PS2™

Ultra-High Performance Sport

SUMMER TIRE

Exceptional performance for drivers demanding precise sport handling. Original equipment on renowned sports cars like BMW M3, Porsche 911 and Chevrolet Corvette ZR1.



Michelin Performance Rating:

8	WEAR LIFE
8	FUEL EFFICIENCY
9	HANDLING
8	BRAKING
7	COMFORT

Benefits of Michelin

- Chosen by the world's top sports car manufacturers.
- High performance cornering.¹
- Outstanding wet and dry performance.

Average User Ratings:

(341 reviews)

Tire Warranties:



Warranties (2 Warranties)



20,000 Mile Manufacturer's Treadwear Limited Warranty

Pilot® Sport PS2™ tires carry an additional 20,000 mile limited warranty for treadwear or mileage.



Standard Limited Warranty (All Michelin® Tires)

All Michelin® tires have a Standard Manufacturer's Limited Warranty, which covers defects in workmanship and materials for the life of the original usable tread, or for 6 years from date of purchase, whichever occurs first. See warranty for details

Available on:

Pilot® Sport PS2™
Speed Rating: [(Y), W, Y, Z]

Tech Specs (105 part numbers)

Please use [Export to excel](#) link in order to download and print technical specification data.

¹ Based on comparisons against the leading competitors in the Ultra-High Performance Summer class.

OE [Vehicle Manufacturer] Sidewall Marking: * = BMW, C1 = Dodge, K1 & K2 = Ferrari, MO & MO1= Mercedes-Benz, N0, N1, N2,N3 & N4 = Porsche, AO & R01 = Audi, TPC= Cadillac and Chevrolet

OE Code [Original Equipment Key]: AC = Acura, AU = Audi, BM = BMW, DC = DaimlerChrysler, FER = Ferrari, GM = GM, L = Lexus, M = Maserati, MB = Mercedes-Benz, P = Porsche

ZP = Zero Pressure Run-Flat Technology

The Load and Speed Index data are not shown on the tire sidewall and are provided for information only purposes

XL = Extra Load, LL = Light Load

>> The sizes shown are average design values for tires measured on specified measuring rim widths. Some tires may vary from this value by +/-3% of the section height (affecting overall diameter), and +/-4% of the section width.

>> Section width varies approximately 0.2" (5mm) for every 0.5" change in rim width.

>> Tread patterns are often tuned to accommodate different tire widths. Tires for a particular dimension of a given tireline may vary in appearance from the tire shown in the photograph.

WARNING: Serious or fatal injury may result from tire failure due to underinflation or overloading. To ensure correct air pressure and vehicle load, refer to vehicle owner's manual or tire information placard on the vehicle. Serious injury or death may result from explosion of tire/rim assembly due to improper mounting. Only tire professionals should mount tires and they should never inflate beyond 40 psi to seat the beads. Before mixing types of tires in any configuration on any vehicle, be sure to check the vehicle owner's manual for its recommendations.

DANGER: Never mount a 17" diameter tire on a 17.5" rim.

Inflation pressure increase must not exceed the maximum pressure branded on the tire sidewall. When a customer requests a replacement tire with a lower speed rating than the original equipment tire, you must clearly communicate to him or her that the handling of the vehicle may be different, and that its maximum speed capability is limited to that of the lowest speed-rated tire on the vehicle. Exceeding the lawful speed limit is neither recommended nor endorsed.

For high-speed driving, additional inflation pressure and possibly reduced tire loading and/or upsizing is required. In the absence of specific recommendations by the vehicle manufacturer, use the following guidelines based on those in the European Tyre and Rim Technical Organization Standards Manual.

For speeds over 160km/h (100 mph), load and inflation must be adjusted according to the table below.

W-Speed Rated Sizes:

Maximum Speed (mph) 118 124 130 136 143 149 155 161 168

Inflation Increase (psi) 0 1.5 3.0 4.5 6.0 7.5 7.5 7.5 7.5

Load Capacity (% of max) 100 100 100 100 100 100 95 90 85

Y-Speed Rated Sizes:

Maximum Speed (mph) 118 124 130 136 143 149 155 161 168 174 180 186

Inflation Increase (psi) 0 0 0 0 1.5 3 4.5 6 7.5 7.5 7.5 7.5

Load Capacity (% of max) 100 100 100 100 100 100 100 100 100 95 90 85

(Y)-Speed Rated Sizes:

Maximum Speed (mph) 118 124 130 136 143 149 155 161 168 174 180 186

Inflation Increase (psi) 0 0 0 0 1.5 3 4.5 6 7.5 7.5 7.5 7.5

Load Capacity (% of max) 100 100 100 100 100 100 100 100 100 95 90 85

For speeds above 186 mph (300 kph), consult your vehicle manufacturer and tire dealer.