



## Pilot® Super Sport

Ultra-High Performance Sport  
Summer Tires

### **Up to 12% better handling than leading competitors.<sup>1</sup>**

Inspired by the same engineering that has powered 13 consecutive victories at 24 Hours of Le Mans.

### **Up to 2x longer lasting than leading competitors<sup>1</sup>**

Optimized through technology of Variable Contact Patch 2.0 and Twaron belt package for long even wear.

### **Better braking than leading competitors<sup>2</sup>**

Bi-compound delivers excellent dry braking using LeMans-inspired compound on the outer shoulder and the latest generation of wet-oriented elastomers on the inner portion of the tread.

#### Performance Ratings

Wear Life	10
Fuel Efficiency	10
Handling	10
Braking	10
Comfort	8

## Mileage Warranties

### 30,000 Mile Manufacturer's Treadwear Limited Warranty

Pilot® Super Sport tires carry an additional 30,000 mile limited warranty for treadwear or mileage.

### Standard Limited Warranty

#### Standard Limited Warranty (All Michelin® Tires)

All Michelin® tires have a Standard Manufacturer's Limited Warranty, which covers defects in workmanship and materials for the life of the original usable tread, or for 6 years from date of purchase, whichever occurs first. See warranty for details.

Tire Size	Load Index / Load Range	Speed Rating	Sidewall	Tread Depth (in 32nds)	UTQG Tread	UTQG Traction	UTQG Temp	Revolutions Per Mile	Max Load, Single (@PSI)	Overall Diameter
215/45ZR17/XL	91	(Y)	BSW	10	300	AA	A	844	1356@50	24.65
225/45ZR17/XL	94	(Y)	BSW	10	300	AA	A	833	1477@50	24.96
235/45ZR17/XL	99	(Y)	BSW	10	300	AA	A	821	1609@50	25.35
245/40ZR17/XL	95	(Y)	BSW	10	300	AA	A	841	1521@50	24.72
225/40ZR18/XL	92	(Y)	BSW	10	300	AA	A	829	1389@50	25.08
225/45ZR18/XL	95	(Y)	BSW	10	300	AA	A	802	1521@50	25.94
225/50ZR18/XL	99	(Y)	BSW	10	300	AA	A	774	1709@50	26.89
235/40ZR18/XL	95	(Y)	BSW	10	300	AA	A	819	1521@50	25.39
245/40ZR18/XL	97	(Y)	BSW	10	300	AA	A	809	1609@50	25.71
245/45ZR18/XL	100	(Y)	BSW	10	300	AA	A	780	1764@50	26.65
255/35ZR18/XL	94	(Y)	BSW	10	300	AA	A	832	1477@50	25
255/40ZR18/XL	99	(Y)	BSW	10	300	AA	A	799	1709@50	26.02
265/40ZR18/XL	101	(Y)	BSW	10	300	AA	A	790	1819@50	26.34
275/35ZR18/XL	99	(Y)	BSW	10	300	AA	A	814	1709@50	25.55
285/35R18/XL	101	(Y)	BSW	10	300	AA	A	804	1819@50	25.87
225/35ZR19/XL	88	(Y)	BSW	10	300	AA	A	824	1235@50	25.24
225/40ZR19/XL	93	(Y)	BSW	10	300	AA	A	797	1432@50	26.1
235/35ZR19/XL	91	(Y)	BSW	10	300	AA	A	817	1356@50	25.47
245/35ZR19/XL	93	(Y)	BSW	10	300	AA	A	807	1432@50	25.79
245/40ZR19/XL	98	(Y)	BSW	10	300	AA	A	778	1653@50	26.73
255/35ZR19/XL	96	(Y)	BSW	10	300	AA	A	799	1565@50	26.02
265/30ZR19/XL	93	(Y)	BSW	10	300	AA	A	822	1432@50	25.31
275/30ZR19/XL	96	(Y)	BSW	10	300	AA	A	814	1565@50	25.55
275/35ZR19/XL	100	(Y)	BSW	10	300	AA	A	783	1764@50	26.57
295/30ZR19/XL	100	(Y)	BSW	10	300	AA	A	799	1764@50	26.02
305/30ZR19/XL	102	(Y)	BSW	10	300	AA	A	792	1873@50	26.26
255/35ZR20/XL	97	(Y)	BSW	10	300	AA	A	770	1609@50	27.01
255/45ZR20/XL	105	(Y)	BSW	10	300	AA	A	716	2039@50	29.06
275/35ZR20/XL	102	(Y)	BSW	10	300	AA	A	755	1873@50	27.56
285/25ZR20/XL	93	(Y)	BSW	10	300	AA	A	813	1432@50	25.59
285/30ZR20/XL	99	(Y)	BSW	7	300	AA	A	777	1709@50	26.77
285/30ZR20/XL	99	(Y)	BSW	10	300	AA	A	777	1709@50	26.77
295/25ZR20/XL	95	(Y)	BSW	10	300	AA	A	805	1521@50	25.83
315/35ZR20/XL	110	(Y)	BSW	7	300	AA	A	726	2336@50	28.66
345/30ZR20	106	(Y)	BSW	10	300	AA	A	716	2094@51	28.14
255/30ZR21/XL	93	(Y)	BSW	10	300	AA	A	769	1432@50	27.05
265/30ZR21/XL	96	(Y)	BSW	10	300	AA	A	762	1565@50	27.28
295/25ZR21/XL	96	(Y)	BSW	10	300	AA	A	776	1565@50	26.81
295/30ZR21/XL	102	(Y)	BSW	10	300	AA	A	743	1873@50	27.99
235/30ZR22/XL	90	(Y)	BSW	10	300	AA	A	754	1322@50	27.6
265/30ZR22/XL	97	(Y)	BSW	10	300	AA	A	735		

1 Based on commissioned third-party testing conducted by TUV Automotive for handling and DEKRA Test Center for longevity of Michelin Pilot Super Sport vs. Bridgestone Potenza RE050A, Continental Sport Contact 3, Dunlop SPSport Maxx GT, Goodyear Eagle F1 Asymmetric, and Pirelli PZero. Specific results quoted vs. Pirelli PZero.

2 Based on commissioned third-party testing conducted by TUV Automotive braking of Michelin Pilot Super Sport vs. Bridgestone Potenza RE050A, Continental Sport Contact 3, Dunlop SP Sport Maxx GT, Goodyear Eagle F1 Asymmetric, and Pirelli PZero.

OE [Vehicle Manufacturer] Sidewall Marking: K1 = Ferrari, MO= Mercedes-Benz  
OE Code [Original Equipment Key]: FER = Ferrari, MB = Mercedes-Benz# The Load and Speed Index data are not shown on the tire sidewall and are provided for information only purposes  
XL = Extra Load>> The sizes shown are average design values for tires measured on specified measuring rim widths. Some tires may vary from this value by +/-3% of the section height (affecting overall diameter), and +/-4% of the section width.>> Section width varies approximately 0.2" (5mm) for every 0.5" change in rim width.>> Tread patterns are often tuned to accommodate different tire widths. Tires for a particular dimension of a given tireline may vary in appearance from the tire shown in the photograph.  
**WARNING:** Serious or fatal injury may result from tire failure due to underinflation or overloading. To ensure correct air pressure and vehicle load, refer to vehicle owner's manual or tire information placard on the vehicle. Serious injury or death may result from explosion of tire/rim assembly due to improper mounting. Only tire professionals should mount tires and they should never inflate beyond 40 psi to seat the beads. Before mixing types of tires in any configuration on any vehicle, be sure to check the vehicle owner's manual for its recommendations.  
**DANGER:** Never mount a 17" diameter tire on a 17.5" rim. Inflation pressure increase must not exceed the maximum pressure branded on the tire sidewall. When a customer requests a replacement tire with a lower speed rating than the original equipment tire, you must clearly communicate to him or her that the handling of the vehicle may be different, and that its maximum speed capability is limited to that of the lowest speed-rated tire on the vehicle. Exceeding the lawful speed limit is neither recommended nor endorsed. For high-speed driving, additional inflation pressure and possibly reduced tire loading and/or upsizing is required. In the absence of specific recommendations by the vehicle manufacturer, use the following guidelines based on those in the European Tyre and Rim Technical Organization Standards Manual. For speed over 160km/h (100 mph), load and inflation must be adjusted according to the table below.  
(Y)-Speed Rated Sizes: Maximum Speed (mph) 118 124 130 136 143 149 155 161 168 174 180 186  
Inflation Increase (psi) 0 0 0 0 1.5 3 4.5 6 7.5 7.5 7.5 7.5  
Load Capacity (% of max) 100 100 100 100 100 100 100 100 100 100 95 90 85  
For speeds above 186 mph (300 kph), consult your vehicle manufacturer and tire dealer