



The all-position radial designed specifically for exceptional performance on recreational vehicles and motor homes.



- Wide, "see-through" grooves promote drainage efficiency to help improve traction on wet surfaces.
- Multi-siping helps deliver dependable grip and long, even wear.
- Enlarged sidewall characters make load/pressure information easier to read, facilitating proper use and maintenance.
- Stable tread with cool running compound helps generate reduced squirm and lower heat for improved handling and durability.

Specifications for Tread Design: **XRV®**

Size	Load Range	Catalog Number	Tread Depth 32nds	Max Speed mph	Loaded Radius		Overall Diameter		Overall Width		Approved Rims	Min. Dual Spacing		Revs per Mile	Max. Tire Load Single				Max. Tire Load Dual			
					in.	mm.	in.	mm.	in.	mm.		in.	m		lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
225/70R19.5	F	58916	13	75	14.9	379	32.0	813	8.7	222	6.00, 6.75	9.7	246	648	3640	95	1650	660	3415	95	1550	660
245/70R19.5	F	67140	14	75	15.5	393	33.3	846	9.6	245	6.75, 7.50	10.7	272	625	4080	95	1850	660	3860	95	1750	660
235/80R22.5	G	87511	16	75	17.4	443	37.1	942	9.2	233	6.75, 7.50	10.3	262	556	4675	110	2120	760	4410	110	2000	760
255/80R22.5	G	59634	16	75	17.9	456	38.2	972	9.9	251	7.50, 8.25	11.2	284	541	5205	110	2360	760	4805	110	2180	760
305/70R22.5	L	93499	16	75	18.1	460	39.1	994	12.3	312	9.00, 8.25	13.5	343	531	7830	120	3550	830	6940	120	3150	830

Note: Rim listed first is the measuring rim.  
 Exceeding the lawful speed limit is neither recommended nor endorsed.  
 Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.  
 Michelin® tires and tubes are subject to a continuous development program. Michelin North America, Inc. reserves the right to change product specifications at any time without notice or obligations.  
 Please consult rim manufacturer's load and inflation limits. Never exceed rim manufacturer's limits without permission of component manufacturer.

**WARNING! SERIOUS INJURY MAY RESULT FROM:**  
 \*TIRE FAILURE DUE TO UNDERINFLATION/OVERLOADING OR MISAPPLICATION -- FOLLOW TIRE PLACARD INSTRUCTIONS IN VEHICLE. CHECK INFLATION PRESSURE FREQUENTLY WITH AN ACCURATE GAUGE  
 \*EXPLOSION OF TIRE/RIM ASSEMBLY DUE TO IMPROPER MOUNTING -- ONLY SPECIALLY TRAINED PERSONS SHOULD MOUNT TIRES. WHEN MOUNTING, USE SAFETY CAGE AND CLIP-ON EXTENSION AIR HOSE TO INFLATE.  
 CONSULT OWNER'S MANUAL FOR ADDITIONAL SAFETY INFORMATION

Load and Inflation Tables: **XRV®**

S = Single configuration, or 2 tires per axle.  
 D = Dual configuration, or 4 tires per axle.

**225/70R19.5 LRF**

		65	70	75	80	85	90	95	MAXIMUM LOAD AND PRESSURE ON SIDEWALL					
PSI		65	70	75	80	85	90	95						
kPa		450	480	520	550	590	620	660						
LBS	SINGLE	5510	5790	6080	6390	6630	6900	7280	S	3640	LBS	at	95	PSI
	DUAL	10400	10880	11440	12000	12460	12980	13660	D	3415	LBS	at	95	PSI
KG	SINGLE	2500	2620	2760	2900	3000	3140	3300	S	1650	KG	at	660	kPa
	DUAL	4720	4920	5200	5440	5640	5880	6200	D	1550	KG	at	660	kPa

If you require information on this tire for RV purposes please go to [www.michelinrvtires.com](http://www.michelinrvtires.com)

### 245/70R19.5 LRF

PSI	80	85	90	95		MAXIMUM LOAD AND PRESSURE ON SIDEWALL		
kPa	550	590	620	660				
LBS	SINGLE	7280	7480	7780	8160		S	4080 LBS at 95 PSI
	DUAL	13660	14060	14620	15440		D	3860 LBS at 95 PSI
KG	SINGLE	3300	3400	3540	3700		S	1850 KG at 660 kPa
	DUAL	6200	6360	6640	7000		D	1750 KG at 660 kPa

If you require information on this tire for RV purposes please go to [www.michelinrvtires.com](http://www.michelinrvtires.com)

### 235/80R22.5 LRG

PSI	70	75	80	85	90	95	100	105	110		MAXIMUM LOAD AND PRESSURE ON SIDEWALL		
kPa	480	520	550	590	620	660	690	720	760				
LBS	SINGLE	6940	7290	7720	7950	8280	8600	8910	9220	9350		S	4675 LBS at 110 PSI
	DUAL	12640	13260	14100	14460	15060	15880	16220	16780	17640		D	4410 LBS at 110 PSI
KG	SINGLE	3140	3300	3500	3600	3760	3900	4040	4180	4240		S	2120 KG at 760 kPa
	DUAL	5720	6000	6400	6560	6840	7200	7360	7600	8000		D	2000 KG at 760 kPa

If you require information on this tire for RV purposes please go to [www.michelinrvtires.com](http://www.michelinrvtires.com)

### 255/80R22.5 LRG

PSI	70	75	80	85	90	95	100	105	110		MAXIMUM LOAD AND PRESSURE ON SIDEWALL		
kPa	480	520	550	590	620	660	690	720	760				
LBS	SINGLE	7750	8140	8600	8880	9240	9610	9950	10300	10410		S	5205 LBS at 110 PSI
	DUAL	14100	14820	15440	16160	16820	17640	18100	18740	19220		D	4805 LBS at 110 PSI
KG	SINGLE	3520	3700	3900	4020	4200	4360	4520	4680	4720		S	2360 KG at 760 kPa
	DUAL	6400	6720	7000	7320	7640	8000	8200	8520	8720		D	2180 KG at 760 kPa

If you require information on this tire for RV purposes please go to [www.michelinrvtires.com](http://www.michelinrvtires.com)

### 305/70R22.5 LRL

PSI	75	80	85	90	95	100	105	110	115	120		MAXIMUM LOAD AND PRESSURE ON SIDEWALL		
kPa	520	550	590	620	660	690	720	760	790	830				
LBS	SINGLE	10750	11320	11880	12440	12990	13540	14080	14600	15140	15660		S	7830 LBS at 120 PSI
	DUAL	19060	20060	21060	22060	23020	24000	24940	25900	26840	27760		D	6940 LBS at 120 PSI
KG	SINGLE	4880	5100	5400	5620	5920	6120	6340	6620	6820	7100		S	3550 KG at 830 kPa
	DUAL	8680	9080	9600	9960	10480	10880	11240	11760	12120	12600		D	3150 KG at 830 kPa

If you require information on this tire for RV purposes please go to [www.michelinrvtires.com](http://www.michelinrvtires.com)

Industry load and inflation standards are in a constant state of change, and Michelin continually updates its product information to reflect these changes. Printed material may not reflect the latest load and inflation standards.

**NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.**