

# **TOYO TIRES**<sup>®</sup>

**DRIVEN TO PERFORM**<sup>®</sup>



## **LIGHT TRUCK & SUV** **OPEN COUNTRY<sup>®</sup> A/T II**

On-/Off-Road All-Terrain Tire

Pavement is optional with these versatile all-terrain tires. They offer over 40% more treadlife than the leading competitors\*, a blatantly aggressive tread design, and a quiet ride. The all-new Open Country A/T II also comes with an industry-leading 65,000-mile warranty and our [No Regrets<sup>®</sup> 45-day, 500-mile trial offer](#).

Xtreme sizes, such as 35x12.5R18, feature a deeper tread depth and a more aggressive tread and shoulder design.

### Warranty

In addition to our [limited warranty](#), the Open Country A/T II comes with the following treadwear warranty:

- P-metric/Metric: 65,000 miles
- LT/Flotation: 50,000 miles

### PERFORMANCE RATINGS\*

- 4.0 Dry Handling
- 4.0 Wet Handling
- 4.0 Off-Road Traction
- 5.0 Tread Life
- 3.5 Ride Comfort
- 3.5 Quiet Ride
- 4.0 Winter Handling
- 3.0 Rolling Resistance



Tire Size	Product Code	Approved Rim Width Range (inch)	Overall Diameter (inch)	Overall Width (inch)	Tread Depth (1/32")	Tire Weight (lbs.)
P215/75R15 100S *	352380	5.5-6.0-7.0	27.7	8.5	12	25.6
P225/75R15 102S *	352370	6.0-7.5	28.3	8.8	13	27.8
P235/75R15 108S XL *	352400	6.0-6.5-8.0	28.9	9.3	13	34.2
LT235/75R15 104/101S C/6 *	352680	6.0-6.5-7.0	28.9	9.3	16	34.4
P265/75R15 112S *	352390	7.0-7.5-9.0	30.7	10.5	13	39
30X9.50R15LT 104S C/6 *	352690	6.5-7.5-8.5	29.5	9.4	16	36.6
31X10.50R15LT 109S C/6 *	352700	7.0-8.5-9.0	30.5	10.6	16	40.2
P215/70R16 99S	352330	5.5-6.5-7.0	27.9	8.7	12	26.9
LT215/85R16 115/112Q E/10	352670	5.5-6.0-7.0	30.4	8.5	15	40.6
P225/70R16 101T	352340	6.0-6.5-7.5	28.4	9	13	28.4
P225/70R16 101T *	352350	6.0-6.5-7.5	28.4	9	13	28.7
P225/75R16 104S	352360	6.0-7.5	29.3	8.8	13	30.6
LT225/75R16 115/112Q E/10	352650	6.0-7.0	29.3	8.8	15	38.4
P235/70R16 104T *	352280	6.0-7.0-8.0	29	9.4	13	29.1
P235/70R16 104T	352270	6.0-7.0-8.0	29	9.4	13	30.6
LT235/85R16 120/116R E/10	352660	6.0-6.5-7.5	31.7	9.3	16	43
P245/70R16 106S	352100	6.5-7.0-8.0	29.5	9.8	13	36.4
P245/70R16 106S *	352110	6.5-7.0-8.0	29.5	9.8	13	34.4
P245/75R16 109S	352120	6.5-7.0-8.0	30.5	9.8	13	34.4
P245/75R16 109S *	352130	6.5-7.0-8.0	30.5	9.8	13	34.4

Tire Size	Product Code	Approved Rim Width Range (inch)	Overall Diameter (inch)	Overall Width (inch)	Tread Depth (1/32")	Tire Weight (lbs.)
LT245/75R16 120/116S E/10	352530	6.5-7.0-8.0	30.5	9.8	16	45
LT245/75R16 120/116S E/10 *	352540	6.5-7.0-8.0	30.5	9.8	16	43.7
LT245/75R16 108/104S C/6	352550	6.5-7.0-6.0	30.5	9.8	16	45
LT245/75R16 108/104S C/6 *	352560	6.5-7.0-8.0	30.5	9.8	16	43.4
255/65R16 109H	352140	7.0-7.5-9.0	29.1	10.2	13	37.6
P255/70R16 109S	352310	6.5-7.5-8.5	30.1	10.2	13	37.7
P255/70R16 109S *	352320	6.5-7.5-8.5	30.1	10.2	13	37.7
P265/70R16 111T	352080	7.0-8.0-9.0	30.6	10.8	13	39.7
P265/70R16 111T *	352090	7.0-8.0-9.0	30.6	10.7	13	39.6
P265/75R16 114T	352290	7.0-7.5-9.0	31.7	10.5	13	41.2
P265/75R16 114T *	352300	7.0-7.5-9.0	31.7	10.5	13	41
LT265/75R16 123/120R E/10	352590	7.0-7.5-8.0	31.7	10.5	16	48.3
LT265/75R16 123/120R E/10 *	352600	7.0-7.5-8.0	31.7	10.5	16	47.2
LT265/75R16 112/109T C/6	352610	7.0-7.5-8.0	31.7	10.5	16	45.2
LT265/75R16 112/109T C/6 *	352620	7.0-7.5-8.0	31.7	10.5	16	48.3
LT285/75R16 126/123R E/10	352630	7.5-8.0-9.0	32.8	11.3	17	53.6
LT285/75R16 126/123R E/10 *	352640	7.5-8.0-9.0	32.8	11.3	17	52.9
LT295/75R16 128R E/10	352820	7.5-8.0-9.5	33.4	11.6	17	63.7
LT305/70R16 124/121R E/10	352750	8.0-9.0-9.5	32.8	12.2	17	67.9
LT315/75R16 127/124R E/10	352770	8.0-8.5-11.0	34.6	12.3	17	71.7
P235/65R17 103H	352050	6.5-7.0-8.5	29.1	9.4	12	34
P235/75R17 108S	352260	6.0-6.5-8.0	30.9	9.3	13	39
LT235/80R17 120/117R E/10	352470	6.0-6.5-7.5	31.8	9.3	16	43.7

Tire Size	Product Code	Approved Rim Width Range (inch)	Overall Diameter (inch)	Overall Width (inch)	Tread Depth (1/32")	Tire Weight (lbs.)
P245/65R17 105T	352020	7.0-8.5	29.4	9.8	13	35.7
P245/65R17 105T *	352030	7.0-8.5	29.5	9.8	13	33.4
P245/70R17 108S	352160	6.5-7.0-8.0	30.6	9.8	13	38.1
LT245/70R17 119/116R E/10	352570	6.5-7.0-8.0	30.6	9.8	16	46.3
LT245/75R17 121/118S E/10	352520	6.5-7.0-7.5	31.5	9.8	16	46.3
P255/70R17 110S	352230	6.5-7.5-8.5	31.1	10.2	13	41.5
P265/65R17 110T	352040	7.5-8.0-9.5	30.5	10.8	13	39
P265/70R17 113S	352000	7.0-8.0-9.0	31.5	10.7	13	41
P265/70R17 113S *	352010	7.0-8.0-9.0	31.5	10.7	13	40.8
LT265/70R17 121/118S E/10	352410	7.0-8.0-8.5	31.7	10.7	16	48.7
LT265/70R17 121/118S E/10 *	352420	7.0-8.0-8.5	31.7	10.7	16	48.7
P285/70R17 117T	352150	7.5-8.5-9.5	32.8	11.5	13	48
LT285/70R17 121/118S E/10	352430	7.5-8.5-9.0	32.8	11.5	16	55.7
LT285/70R17 121/118S E/10 *	352440	7.5-8.5-9.0	32.8	11.5	16	50.5
LT285/75R17 121/118S E/10	352790	7.5-8.0-9.5	33.9	11.3	17	63.1
35X12.50R17LT 121R E/10	352810	8.5-10.0-11.0	34.5	12.5	17	69.9
255/55R18 109H XL	352220	7.0-8.0-9.0	29	10.4	13	37.7
P255/70R18 112T	352250	6.5-7.5-8.5	32.1	10.2	13	45
P265/60R18 109T	352240	7.5-8.0-9.5	30.5	10.7	13	40.8
P265/65R18 112S	352200	7.5-8.0-9.5	31.5	10.7	13	43.9
P265/70R18 114S	352180	7.0-8.0-9.0	32.6	10.7	13	49.6
P275/65R18 114T	352070	7.5-8.0-9.5	32.1	11	13	50.7
LT275/65R18 123/120S E/10	352480	7.5-8.0-9.0	32.1	11	16	52.8

Tire Size	Product Code	Approved Rim Width Range (inch)	Overall Diameter (inch)	Overall Width (inch)	Tread Depth (1/32")	Tire Weight (lbs.)
LT275/65R18 123/120S E/10 *	352490	7.5- <b>8.0</b> -9.0	32.1	11	16	50.3
LT275/65R18 113/110T C/6 *	352510	7.5- <b>8.0</b> -9.0	32.1	11	16	50.3
LT275/65R18 113/110T C/6	352500	7.5- <b>8.0</b> -9.0	32.1	11	16	52.7
LT275/70R18 125/122S E/10	352450	7.0- <b>8.0</b> -8.5	33.2	11	16	53.1
LT275/70R18 125/122S E/10 *	352460	7.0- <b>8.0</b> -8.5	33.2	11	16	50.9
285/60R18 120S XL	352190	8.0- <b>8.5</b> -10.0	31.5	11.5	14	53.8
LT285/65R18 125/122S E/10	352720	8.0- <b>8.5</b> -10.0	32.6	11.5	17	58
LT285/75R18 129/126S E/10	352780	7.5- <b>8.0</b> -9.5	34.8	11.3	17	65
LT325/60R18 124/121S E/10	352760	9.0- <b>9.5</b> -12.0	33.3	13	17	65.9
35X12.50R18LT 123R E/10	352710	8.5- <b>10.0</b> -11.0	34.5	12.5	17	80.7
P275/55R20 111S	352170	7.5- <b>8.5</b> -9.5	31.9	11.2	13	45.9
P275/60R20 114T	352060	7.5- <b>8.0</b> -9.5	33	10.9	13	43.4
LT275/65R20 126/123S E/10	352580	7.5- <b>8.0</b> -9.5	34.1	11	16	56.7
LT285/55R20 122/119S E/10	352800	8.0- <b>9.0</b> -10.0	32.4	11.7	16	59.3
305/50R20 120S XL	352210	8.5- <b>9.5</b> -11.0	32	12.4	14	51.2
LT305/55R20 121/118S E/10	352740	8.5- <b>9.5</b> -11.0	33.2	12.4	16	73.9
35X12.50R20LT 121R E/10	352730	8.5- <b>10.0</b> -11.0	34.5	12.5	17	78.9
LT325/50R22 122R E/10	352830	9.0- <b>10.0</b> -12.0	34.8	13.2	17	68.6

Bold designates measuring rim width

RD = Reinforced

XL = Extra load

For Light Truck Tires: \* White letter styling

**Light Truck Construction Elements:** Tread: 3P = 3-Ply Polyester Casing, 2P = 2-Ply Polyester Casing, 2S = 2 Steel Belts, 2N = 2 Nylon Cap Plies, 1N = 1 Nylon Cap Ply

**Sidewall:** 2P = 2 Ply Polyester, 3P = 3 Ply Polyester

All Toyo brand tires are subject to continuous development. Toyo Tire U.S.A. Corp. reserves the right to change construction, materials or specifications without notice or obligation. Contact your Toyo Tires dealer or Toyo Tires for current information.