



Tire Size	Load / Speed	Load ID	Sidewall	Product Code	Approved Rim Width Range (in.)	Weight (lbs.)	Tread Depth (1/32")	Inflated Overall Diameter (in.)	Inflated Overall Width (in.)	Max Load Single / Dual (lbs.)	Max Pressure Single / Dual (PSI)	UTQG	Revs Per Mile	Tread Construction
31X10.50R15LT	109Q	C	BSW	360490	7.0-8.5-9.0	55	19.1	31.1	10.7	2270 / -	50 / -	N/A	667	3P+2S+2N
33X10.50R15LT	114P	C	BSW	360470	7.0-8.5-9.0	57	19.1	32.8	10.9	2600 / -	50 / -	N/A	632	3P+2S+2N
33x12.50R15LT	108P	C	BSW	360100	8.0-10.0-11.0	69	21.0	33.0	12.8	2205 / -	35 / -	N/A	628	2P+2S+2N
33X13.50R15LT	109Q	C	BSW	360290	8.5-11.0	75	21.0	33.1	13.9	2270 / -	35 / -	N/A	628	2P+2S+2N
35X13.50R15LT	114Q	C	BSW	361000	8.50-11.0	79	21.0	34.8	14.4	2600 / -	35 / -	N/A	596	2P+2S+2N
37X14.50R15LT	120Q	C	BSW	360260	10.0-12.0	94	21.0	36.7	15.6	3080 / -	35 / -	N/A	566	3P+2S+2N
LT235/85R16	120/116P	E	BSW	360440	6.0-6.5-7.5	52	18.4	32.0	9.4	3042 / -	80 / -	N/A	648	3P+2S+2N
LT245/75R16	120/116P	E	BSW	360450	6.5-7.0-8.0	52	18.4	30.7	9.9	3042 / -	80 / -	N/A	674	3P+2S+2N
LT255/85R16 (33X10.00R16)	123/120P	E	BSW	360460	6.5-7.0-8.0	60	18.9	33.5	10.2	3415 / -	80 / -	N/A	619	3P+2S+2N
LT265/75R16	123P	E	BSW	360320	7.0-7.5-8.0	58	18.9	31.8	10.8	3415 / -	80 / -	N/A	651	3P+2S+2N
LT285/75R16 (33X11.50R16)	126P	E	BSW	360280	7.5-8.0-9.0	68	19.1	33.0	11.6	3740 / -	80 / -	N/A	628	3P+2S+2N
LT305/70R16 (33.0X12.00R16)	124P	E	BSW	360110	8.0-9.0-9.5	72	20.0	33.0	12.2	3525 / -	65 / -	N/A	628	3P+2S+2N
LT315/75R16 (35X12.50R16)	127Q	E	BSW	360230	8.0-8.5-10.0	76	21.0	34.9	12.9	3860 / -	65 / -	N/A	595	3P+2S+2N
LT385/70R16 (38X14.50R16)	130Q	D	BSW	360480	10.0-11.0-12.0	97	21.0	37.7	15.6	4190 / -	50 / -	N/A	550	3P+2S+2N
LT265/70R17	121P	E	BSW	360130	7.0-8.0-8.5	63	18.9	32.0	10.8	3195 / -	80 / -	N/A	648	3P+2S+2N
LT285/70R17	121/118P	E	BSW	360650	7.5-8.5-9.0	66	18.9	33.0	11.5	3195 / 2910	80 / 80	N/A	630	3P+2S+2N
LT285/75R17 (34X11.50R17)	121P	E	BSW	360430	7.5-8.0-9.5	71	19.1	34.1	11.6	3195 / -	80 / -	N/A	608	3P+2S+2N
LT295/70R17 (33X11.50R17)	128P	E	BSW	360360	7.5-8.5-10.0	73	19.4	33.5	12.0	3970 / -	80 / -	N/A	619	3P+2S+2N
35X12.50R17LT	125Q	E	BSW	360310	8.5-10.0-11.0	83	21.0	34.8	13.2	3640 / -	65 / -	N/A	596	3P+2S+2N
37X13.50R17LT	131Q	E	BSW	360270	8.5-11.0	93	21.0	37.0	14.6	4300 / -	65 / -	N/A	560	3P+2S+2N
40X13.50R17LT	121Q	C	BSW	361010	8.5-11.0	106	21.0	39.7	14.4	3195 / -	35 / -	N/A	522	3P+2S+2N
LT275/65R18	123/120P	E	BSW	360620	7.5-8.0-9.0	65	18.9	32.3	11.0	3415 / 3085	80 / 80	N/A	643	3P+2S+2N
LT275/70R18 (33X11.00R18)	125P	E	BSW	360120	7.0-8.0-8.5	66	19.1	33.6	11.0	3640 / -	80 / -	N/A	617	3P+2S+2N
LT285/70R18 (34X11.50R18)	127/124Q	E	BSW	360590	7.5-8.5-9.5	69	18.9	34.1	11.4	3860 / 3525	80 / 80	N/A	609	3P+2S+2N
LT285/75R18 (35X11.5R18)	129P	E	BSW	360420	7.5-8.0-9.5	71	19.1	35.1	11.6	4080 / -	80 / -	N/A	591	3P+2S+2N
LT295/70R18	129/126P	E	BSW	360640	7.5-8.5-10.0	73	19.4	34.5	11.8	4080 / 3750	80 / 80	N/A	602	3P+2S+2N
LT315/70R18 (36X13.00R18)	127/124Q	E	BSW	360560	8.0-9.5-11.0	82	20.7	35.7	13.0	3860 / 3525	65 / 65	N/A	581	3P+2S+2N
33X12.50R18LT	118Q	E	BSW	360340	8.5-10.0-11.0	75	21.0	33.0	12.7	2910 / -	65 / -	N/A	630	3P+2S+2N
35X12.50R18LT	123Q	E	BSW	360090	8.5-10.0-11.0	81	21.0	35.0	13.2	3415 / -	65 / -	N/A	593	3P+2S+2N
37X13.50R18LT	124Q	D	BSW	360300	8.5-11.0	93	21.0	37.0	14.2	3525 / -	50 / -	N/A	560	3P+2S+2N
38x13.50R18LT	126Q	D	BSW	360380	8.50-11.0	97	21.0	37.7	14.3	3750 / -	50 / -	N/A	550	3P+2S+2N
38X15.50R18LT	128Q	D	BSW	360180	11.0-12.0-13.0	106	21.0	37.7	15.9	3970 / -	50 / -	N/A	550	3P+2S+2N
LT275/55R20	115/112P	D	BSW	360670	7.5-8.5-9.5	68	19.1	32.1	11.2	2680 / 2470	65 / 65	N/A	647	3P+2S+2N
LT275/65R20 (34X11.00R20)	126P	E	BSW	360410	7.5-8.0-9.5	71	19.1	34.5	11.0	3750 / -	80 / -	N/A	601	3P+2S+2N
LT295/55R20	123/120P	E	BSW	360610	8.0-9.5-10.0	72	19.4	33.0	12.2	3415 / 3085	80 / 80	N/A	630	3P+2S+2N
LT295/60R20	126/123P	E	BSW	360660	8.0-8.5-10.0	80	19.4	34.2	11.8	3750 / 3415	80 / 80	N/A	608	3P+2S+2N
LT295/65R20	129/126P	E	BSW	360630	8.0-8.5-10.0	75	19.4	35.4	11.8	4080 / 3750	80 / 80	N/A	588	3P+2S+2N
LT315/60R20 (35X12.50R20)	125Q	E	BSW	360510	8.5-9.5-11.0	78	20.7	35.0	12.6	3640 / 3305	65 / 65	N/A	593	3P+2S+2N
33X12.50R20LT	114Q	E	BSW	360330	8.5-10.0-11.0	72	21.0	33.0	12.6	2600 / -	65 / -	N/A	630	3P+2S+2N
35X12.50R20LT	121Q	E	BSW	360240	8.5-10.0-11.0	80	21.0	35.0	13.0	3195 / -	65 / -	N/A	592	3P+2S+2N
37X13.50R20LT	127Q	E	BSW	360220	8.5-11.0	94	21.0	37.0	14.0	3860 / -	65 / -	N/A	560	3P+2S+2N

38X13.50R20LT	124Q	D	BSW	360390	8.50- <b>11.0</b>	100	21.0	37.7	14.3	3525 / -	50 / -	N/A	550	3P+2S+2N
38X15.50R20LT	125Q	D	BSW	360190	11.0- <b>12.0</b> -13.0	101	21.0	37.7	15.9	3640 / -	50 / -	N/A	550	3P+2S+2N
40X15.50R20LT	130Q	D	BSW	360370	11.0- <b>12.0</b> -13.0	112	21.0	39.7	15.9	4190 / -	50 / -	N/A	522	3P+2S+2N
33X12.50R22LT	109Q	E	BSW	360520	8.5- <b>10.0</b> -11.0	71	18.9	33.0	12.4	2270 / -	65 / -	N/A	629	3P+2S+2N
35X12.50R22LT	117Q	E	BSW	360540	8.5- <b>10.0</b> -11.0	80	21.0	35.0	12.8	2835 / -	65 / -	N/A	593	3P+2S+2N
37X13.50R22LT	123Q	E	BSW	360210	8.5- <b>11.0</b>	90	21.0	37.0	14.0	3420 / -	65 / -	N/A	560	3P+2S+2N
40X15.50R22LT	127Q	D	BSW	360200	11.0- <b>12.0</b> -13.0	110	21.0	39.7	15.9	3860 / -	50 / -	N/A	522	3P+2S+2N
37X13.50R24LT	120Q	E	BSW	360350	8.5- <b>11.0</b>	89	21.0	37.0	13.6	3085 / -	65 / -	N/A	561	3P+2S+2N
40X15.50R24LT	128P	E	BSW	360680	11.0- <b>12.0</b> -14.0	106	21.0	39.8	15.4	3970 / -	65 / -	N/A	522	3P+2S+2N

 [Print Complete](#)

Bold designates measuring rim width

SL = Standard Load, XL = Extra Load, RD = Reinforced, TD = Tuff Duty, XT = Xtreme, BSW = Black Sidewall, OWL = Outline White Lettering.

Speed rating M = 81 mph, N = 87 mph, P = 93 mph, Q = 99 mph, R = 106 mph, S = 112 mph, T = 118 mph, H = 130 mph, V = 149 mph, W = 168 mph, Y = 186 mph, (Y) = 195 mph

LT tires with: "C" load range have a 6-ply rating, "D" have a 8-ply rating, "E" have a 10-ply rating.

**Tread Construction:** 3P = 3-ply polyester casing, 2P = 2-ply polyester casing, 2S = 2-steel belts, 2N = 2-nylon cap plies, 1N = 1-nylon cap ply

**Sidewall Construction:** 2P = 2-ply polyester, 3P = 3-ply polyester

All Toyo brand tires are subject to continuous development. Toyo Tire U.S.A. Corp. reserves the right to change construction, materials or specifications without notice or obligation.

Contact your Toyo Tires dealer or Toyo Tires for current information.